



Corepro - LED HID HPL



TForce Core LED HPL 36W E40 830 FR

Philips TrueForce Core LED HPL lamps are an easy, LED solution with a short payback to replace High Intensity Discharge (HID) lamps. This new generation of LED Core Post–Top lamps brings all the energy–efficiency and long-lifetime benefits of LED to HID replacement, while delivering instant saving for a low initial investment. Furthermore, TrueForce CorePro LED HPL lamps are designed to have the same lamp size and light distribution as their HID alternatives. And thanks to our high-power LED filament technology, you'll never know the difference. Plus, their unique IP65 design means that TrueForce Core LED HPL Post–Top lamps can be used for outdoor, as well as indoor applications.

Warnings and Safety

• Installation should always be performed by a qualified electrician or installer. Use the installation guide for instructions.

Product data

General Information	
Cap-Base	E40 [E40]
Nominal lifetime	25,000 hour(s)
Switching Cycle	15,000
Lighting Technology	LED
Flux measurement reference	Sphere
CE mark	Yes
EU RoHS compliant	Yes
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	5,500 lumen

Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	152.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Flickering value (PstLM)	1
Stroboscopic effect value (SVM)	1.6
Photobiological safety according to EN 62471	RGO
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz


Datasheet, 2023, November 3 data subject to change

Corepro - LED HID HPL

Power Consumption	36 W
Lamp Current (Nom)	165 mA
Wattage Equivalent	200 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V
Temperature	
Ambient temperature range	-30 to +45 ℃
T-Case Maximum (Nom)	59 ℃
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Shape	ED90 [ED 90mm]


Approval and Application	
Energy Efficiency Class	D
Energy Consumption kWh/1000 h	36 kWh
EPREL Registration Number	403656
Product Data	
Full product code	871951429931300
Order product name	TForce Core LED HPL 36W E40 830 FR
Order code	929002481402
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929002481402
Full product name	TForce Core LED HPL 36W E40 830 FR
EAN/UPC - Case	8719514299320
EAN/UPC - Product/Case	8719514299313


Dimensional drawing



Product	D	С
TForce Core LED HPL 36W E40 830 FR	90 mm	230 mm

Photometric data






Spectral Power Distribution Colour - TForce Core LED HPL 36W E40 830 FR

General uniform lighting - TForce Core LED HPL 36W E40 830 FR


Corepro - LED HID HPL


Photometric data



Light Distribution Diagram - TForce Core LED HPL 36W E40 830 FR

Lifetime





Life Expectancy Diagram - TForce Core LED HPL 36W E40 830 FR

Lumen Maintenance Diagram - TForce Core LED HPL 36W E40 830 FR



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.