

MasterConnect LEDtube EM/mains T8

MasterConnect LEDtube IA 1500mm UO 25W840 T8

Introducing MasterConnect LED lamps – smart retrofit LED lamps that give you an easy and seamless way to upgrade to connected lighting. Simply set up with an intuitive app, MasterConnect LED lamps can be programmed to maximise energy savings, while providing wireless and automated light for your comfort and convenience. What's more, it is fully scalable and upgradable. If you want to enjoy further benefits, such as remote control or management dashboard, you can simply keep the currently installed lamps and add a gateway to experience all the advantages of a cloud-based system. There's no better way to take lighting solutions to the next level.

Product data

General Information					
Cap base	G13 [Medium Bi-Pin Fluorescent]				
EU RoHS compliant	Yes				
Nominal lifetime (nom.)	60000 h				
Switching cycle	200,000X				
Technical type	25-58W				
Light Technical					
Colour Code	840 [CCT of 4,000 K]				
Beam Angle (Nom)	160 °				
Luminous flux (nom.)	3700 lm				
Colour designation	Cool White (CW)				
Correlated Colour Temperature (Nom)	4000 K				
Luminous efficacy (rated) (nom.)	148.00 lm/W				

Colour consistency	<6				
Colour rendering index (nom.)	83				
LLMF at end of nominal lifetime (nom.) 70 %					
Operating and Electrical					
Input frequency	50 to 60 Hz				
Power (Rated) (Nom)	25 W				
Lamp current (max.)	117 mA				
Lamp current (min.)	108 mA				
Starting time (nom.)	0.5 s				
Warm-up time to 60% light (nom.)	0.5 s				
Power factor (nom.)	0.9				
Voltage (Nom)	220-240 V				


Datasheet, 2021, June 17 data subject to change

MasterConnect LEDtube EM/mains T8

Temperature			
T-ambient (max.)	45 °C		
T-ambient (min.)	-20 °C		
T storage (max.)	65 °C		
T storage (min.)	-40 °C		
T-Case maximum (nom.)	65 °C		
Controls and Dimming			
Dimmable	Wireless Dim		
Mechanical and Housing			
Product length	1500 mm		
Approval and Application			
Energy efficiency label (EEL)	A++		
Energy-saving product	Yes		


Approval marks	RoHS compliance CE marking KEMA Keu		
	certificate		
Energy consumption kWh/1,000 hours	25 kWh		
Product Data			
Full product code	871869966976800		
Order product name	MasterConnect LEDtube IA 1500mm UO		
	25W840 T8		
EAN/UPC – product	8718699669768		
Order code	66976800		
SAP numerator – quantity per pack	1		
Numerator – packs per outer box	10		
SAP material	929002210802		
SAP net weight (piece)	0.450 kg		


Dimensional drawing



Product	D1	D2	A1	A2	A3
MasterConnect LEDtube	25.8	28 mm	1498.7	1505.8	1512.9
IA 1500mm UO 25W840	mm		mm	mm	mm
T8					

Photometric data






MC LEDtube 25W G13 3700lm 840

MC LEDtube G13 840


MasterConnect LEDtube EM/mains T8


Photometric data




MC LEDtube G13

Lifetime






LEDtube_60K_FailureRate



LEDtube_60K_LifetimeVsTc




MC LEDtube 25W 60K LumenVsTc

LEDtube_60K

MasterConnect LEDtube EM/mains T8

Lifetime



LEDtube_60K

