

# PRODUCT DATASHEET ENDURA STYLE LANTERN FLARE Wall 7W

ENDURA STYLE FLARE | Stainless steel wall luminaires with indirect illumination





## **TECHNICAL DATA**

## Electrical data

Nominal wattage	7.00 W
Operating mode	Mains voltage
Nominal voltage	220240 V
Power factor $\lambda$	> 0,5


#### Photometrical data

Color temperature	3000 K
Luminous flux	470 lm
Luminous efficacy	67 lm/W
Light color	Warm White
Standard deviation of color matching	< 6 sdcm
Color rendering index Ra	≥80

# Light technical data

Beam angle	230.00 °

# Dimensions & weight



Length	98.00 mm
Height	331.00 mm
Width	68.00 mm
Product weight	850.00 g

## Colors & materials

Body material	Aluminum
Product color	Dark gray



Housing color	Dark gray
Cover material	Polycarbonate (PC)

# Temperatures & operating conditions

# Lifespan

Number of switching cycles	12500
Lifespan L70/B50 at 25 °C	25000 h

# Additional product data

Mounting type	Surface
Mounting location	Wall

# **Capabilities**

Dimmable	No
Type of connection	Terminal, 3-Pole (L, N, PE)
LEDmod replaceable	Not replaceable

#### Certificates & standards

Protection class	I
Type of protection	IP44
Standards	CE / EAC / REACH / RoHS

#### **DOWNLOAD DATA**

	DOWNLOAD DATA
POF	User instruction ENDURA STYLE LANTERN FLARE
	Tender documents Tender Text 4058075478039

## **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075478039	Folding box 1	117 mm x 87 mm x 354 mm	929.00 g	3.60 dm <sup>3</sup>
4058075478046	Shipping box 4	368 mm x 248 mm x 199 mm	4121.00 g	18.16 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.