

PRODUCT DATASHEET ENDURA STYLE CRYSTAL Torch 4.5W

ENDURA STYLE CRYSTAL | Stainless steel wall luminaires and bollards with indirect illumination





TECHNICAL DATA


Electrical data

Nominal wattage	4.50 W
Operating mode	Mains voltage
Nominal voltage	220240 V
Power factor λ	> 0,5

Photometrical data

Color temperature	3000 K	
Luminous flux	400 lm	
Luminous efficacy	89 lm/W	
Light color	Warm White	
Standard deviation of color matching	< 6 sdcm	
Color rendering index Ra	≥80	

Dimensions & weight



Length	80.00 mm
Height	225.00 mm
Width	80.00 mm
Product weight	860.00 g

Colors & materials

Body material	Steel	
Product color	Steel	
Housing color	Steel	
Cover material	Polymethylmethacrylate (PMMA)	

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

Lifespan

Number of switching cycles	12500
Lifespan L70/B50 at 25 °C	25000 h

Additional product data

Mounting type	Surface
Mounting location	Wall

Capabilities

Dimmable	No	
Type of connection	Terminal, 3-Pole (L, N, PE)	
LEDmod replaceable	Not replaceable	

Certificates & standards

Protection class	1
Type of protection	IP44
Standards	CE / EAC / REACH / RoHS

DOWNLOAD DATA

	DOWNLOAD DATA
PDF	User instruction ENDURA STYLE CRYSTAL TORCH
	Tender documents Tender Text 4058075474215
PDF	Packaging insert Legal insert

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075474215	Folding box 1	107 mm x 107 mm x 249 mm	938.00 g	2.85 dm ³
4058075474222	Shipping box	335 mm x 230 mm x 265 mm	6102.00 g	20.42 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.