# PRODUCT DATASHEET SMART+ ZB TIBEA Pendant Tunable White

TIBEA E27 Tunable White | Indoor luminaire including LED lamp for indirect lighting with Zigbee technology



# Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)

#### **Product benefits**

- Stylish and modern design
- Indirect lighting for a relaxing atmosphere
- Wireless control via app or voice control
- Easy to install and use
- Contains no mercury

#### **Product features**

- Controllable via compatible smart home system (gateway and app) or SMART+ Switch
- Adjustable color temperature via Tunable White: 2,700...6,500 K
- Dimmable
- As ceiling, pendant and mini type-version available
- Network protocol: ZigBee
- Lifetime: up to 20,000 h
- For full functionality, connection to a compatible smart home System (gateway and app) required



# **TECHNICAL DATA**

# **Electrical data**


Nominal wattage	22.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor $\lambda$	≥0.90
Protection class	Ш
Operating mode	Integrated LED driver

# Photometrical data

Luminous flux	1250 lm	
Luminous efficacy	57 lm/W	
Color temperature	27006500 K	
Light color (designation)	Tunable White	
Color rendering index Ra	> 80	
Standard deviation of color matching	≤6 sdcm	

# **Dimensions & Weight**

Diameter	350.00 mm
Height	69.00 mm
Product weight	960.00 g



Product line drawing with numbers

Product line drawing with numbers

#### Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Mercury content	0.0 mg

# Application & Mounting

Ambient temperature range -20+40 °C		
Type of connection	Terminal, 2-Pole (L, N)	
Type of protection	IP20	
Dimmable	Yes	
Mounting type	Suspended	
Mounting location	Ceiling	
Application environment	Indoor	
With light source	Yes	
Holder designation	E27	

# Lifespan

Lifespan L70/B50 at 25 °C	20000 h
---------------------------	---------



Lifespan L80/B10 at 25 °C	20000 h
Lifespan L90/B10 at 25 °C	20000 h
Number of switching cycles	100000

# **Certificates & Standards**

Standards	CE

# **EQUIPMENT / ACCESSORIES**

- Control via app or voice control requires compatible Smart home system

#### **DOWNLOAD DATA**

	DOWNLOAD DATA
POF	User instruction
1	Tender documents
PDF	Declarations of conformity

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075345362	Folding box 1	109 mm x 465 mm x 361 mm	1408.00 g	18.30 dm³
4058075345379	Shipping box 2	570 mm x 460 mm x 230 mm	4529.00 g	60.31 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.