

60T4QCL 60W 24V 12/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Technical data

General product information

Product Number	58729
Product Name	60T4QCL 60W 24V 12/CS 1/SKU
Ordering Abbreviation	60T4QCL 60W 24V 12/CS 1/SKU
Application	Medical Overhead Illumination

Electrical data

Nominal Wattage	60 W
Nominal Voltage	24 V

Light technical data

Luminous Flux	1280 lm
Color Temperature	3100 K
Color Rendering Index	100
Average Rated Life	500 h

Physical attributes

Base	BA15D
Bulb Shape	T12
Maximum Overall Length (in)	2.362 in
Maximum Overall Length (mm)	63.8 mm
Length l (in)	2.362 in
Length l (mm)	63.8 mm
Length l max. (in)	2.362 in
Length l max. (mm)	63.8 mm
Diameter d (in)	0.567 in
Diameter d (mm)	14.40 mm
Distance a (in)	1.374 in
Distance a (mm)	37.1 mm
Filament	CC-6

Additional product data

Operating Position	Any
Total surface inside 1: appearance (cold)	CLEAR
Class	C (gas)
Lamp Type	SINGLE END

Product datasheet

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
58729	0046135587290	Folding box (SKU)	1	1.3 in x 1.3 in x 3.5 in	0.1 lb
58729	10046135587297	Shipping box (Case)	12	5.6 in x 4.5 in x 4.4 in	1.3 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.