

## PL-CN50-COB- 1400-930-15D-G2

PrevaLED COIN 50 COB G2 | LED modules with integrated optics and heat sink



### Product family features

- Color consistency < 2 SDCM
- TM30 compliant
- High flux output up to 1500 lm
- Beam angle: 15°, 24°, 40°
- Type of protection: IP20

### Product family benefits

- Compatible with conventional MR16 lamps
- Precise optical control and free from multi-shadow issue
- Replaceable front cover to maximize optics flexibility and future extension
- Dual mode options in High-Output (HO) and High-Efficacy (HE)

### Areas of application

- Retail, shop, restaurant, hospitality
- High-end residential
- Suitable for indoor applications
- Connecting multiple modules in parallel on one LED driver is not permitted
- Connecting multiple modules in series on one LED driver is not recommended
- Do not use in sealed fixtures
- Avoid covering the lens with dust or any object



# Product datasheet

## Technical data

### Electrical data

Nominal current	0.35 A
Nominal voltage	34.4 V
Type of current	DC
On-mode power	12.1 W
Energy consumption in on-mode	12.1 kWh/1000h

### Photometrical data



Luminous efficacy	92 lm/W
Light color (designation)	3000 K
Color rendering index Ra	90
Correlated color temperature CCT	3000 K
Peak luminous intensity	7554
Colour consistency (McAdam ellipses)	2
Useful luminous flux ( $\Phi_{use}$ ) [GMS]	1032 lm <sup>1)</sup>

<sup>1)</sup> 90°

### Light technical data

Starting time	< 0.5 s
Warm-up time (60 %)	< 2.00 s

### Dimensions & weight



Diameter	50.0 mm
Product weight	90.00 g
Height	55 mm
Length	50 mm
Width	50 mm

## Product datasheet

### Colors & materials

Heatsink color	Grey
----------------	------

### Temperatures & operating conditions

Performance temp. acc. to IEC 62717	70 °C
Maximum temperature at tc test point	90 °C
Ambient temperature range	-25...+40 °C
Temperature range at storage	-40...80 °C

### Lifespan

Number of switching cycles	15000
Lumen maintenance factor LMF [GMS]	96
L70B50 lifetime [GMS]	50000 h

### Additional product data

Product remark	Modules perfectly matched to OSRAM OPTOTRONIC LED drivers (see relevant table)/For current photometric data and important safety, installation and application information (see <a href="http://www.osram.com/led-systems">www.osram.com/led-systems</a> ),/All the technical parameters apply to the entire module. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values/Tolerance for optical and electrical data: +/-10%
Lighting technology used [GMS]	LED

### Certificates & standards

Standards	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE
Type of protection	IP20
Energy efficiency class	F

### Logistical data

Commodity code	853951000000
----------------	--------------




### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)

## Product datasheet

<b>Date of Declaration</b>	20-05-2022
<b>Primary Article Identifier</b>	4062172227162
<b>Candidate List Substance 1</b>	No declarable substances contained
<b>Declaration No. in SCIP database</b>	No declarable substances contained

### Download Data

File	
 Certificates PL CN50 COB 1400 G2 ENEC 181121	
 CAD data PL CN50 G2 STEP 041121	
 IES data PL CN50 COB 1400 930 15D G2 IES 041121	

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172227162	PL-CN50-COB- 1400-930-15D-G2	Shipping carton box 20	268 mm x 110 mm x 138 mm	4.07 dm <sup>3</sup>	2156.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Accessories Optional

Product description	Accessory name	Accessory code
PL-CN50-COB- 1400-930-15D-G2	PL-CN50 -ROUND-RING	▶ 4062172134842
PL-CN50-COB- 1400-930-15D-G2	BLACK COVER FOR COIN 50 COB G2	▶ 4062172251808

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.