

# PRODUCT DATASHEET CONVERSION KIT + LED TUBE T5 AC HE35 P 1449 mm 18W 840

LED TUBE T5 CONVERSION KIT DOUBLE LAMP | T5 LED tubes including conversion kit for double lamp luminaires



# Areas of application

- General illumination within ambient temperatures from -20...+45 °C
- Offices, public buildingsSupermarkets and department stores
- Industry

# Product benefits

- Only around 5 minutes per luminaire needed for rewiring
- No ECG compatibility issues
- No ECG maintenance necessary
- No bending thanks to glass technology
- Shatter protection thanks to special PET coating
- High luminous flux for sophisticated lighting tasks

# Product features

- Contains 10 LED TUBE T5 220-240V AC LED tubes and 5 conversion kits for double-lamp luminaires
- Conversion kit contains all necessary material for conversion of ECG luminaires to AC mains
- Detailed step-by-step instruction for guaranteed TÜV-certification available
- LED replacement for T5 fluorescent lamps with G5 base on AC mains



April 04, 2024, 09:52:24 CONVERSION KIT + LED TUBE T5 AC HE35 P 1449 mm 18W 840

- Lamp tube made of glass with splinter protection e.g. for food industry applications
- High color consistency:  $\leq$  5 SDCM
- Lifetime: up to 50,000 h
- Low flicker according to EU 2019-2020 (SVM  ${\leq}0{,}4$  / PstLM  ${\leq}$  1)
- Type of protection: IP20

## **TECHNICAL DATA**

# **Electrical data**

Nominal wattage	18 W
Nominal voltage	220240 V
Nominal current	82 mA

# Photometrical data

Luminous flux	2800 lm
Luminous efficacy	155 lm/W
Light color	840

## Light technical data

Beam angle	190 °

# **Dimensions & Weight**

Product weight 2033.0	Jd
-----------------------	----

## Additional product data

	This product contains the following LED Tube as a light source: LED	
Product remark	TUBE T5 AC HE35 P 1449 mm 18W 840, EAN: 4058075824256, LED	
	tube EEC: D	

## Certificates & Standards

Type of protection IP20
-------------------------

# Country-specific categorizations

Order reference	LEDTUBE T5AC HE

# Safety advice

- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.

- Not suitable for operation with electronic control gear.

- Not suitable for emergency lighting

# DOWNLOAD DATA

Documents and certificates

POF

Installation guide

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854108518	Shipping box 1	1,515 mm x 150 mm x 95 mm	2961.00 g	21.59 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **References / Links**

- For current information see www.ledvance.com/ledtube

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.