



CoreLine Highbay Gen5

BY120P G5 LED105S/865 PSU NB

CoreLine Highbay Gen5, 67 W, 10500 lumen, 6500 K, Narrow beam, IP65, IK08

CoreLine Highbay Gen5 delivers on the CoreLine promise of innovative, easy-to-use and high-quality luminaires. A reliable, highly-efficient luminaire with a very long-lifetime, it delivers great energy savings and requires less maintenance. At the same time, CoreLine Highbay is very easy to handle. The luminaire can be installed on your existing grid and the electrical connection is a straightforward task, with no need to open the luminaire and an external IP65 connector. With a choice of two beam angles: narrow and wide beam, you can adjust your lighting plan to suit your exact needs. This range also includes Interact Ready luminaires with integrated wireless communications and integrated movement and daylight sensors. So CoreLine Highbay Gen5 is ready to be used with any Interact connected lighting system.

Product data

General Information	
Light source replaceable	No
CE mark	Yes
Number of gear units	1 unit
Driver included	Yes
Flammability mark	For mounting on normally flammable surfaces
Glow-wire test	Temperature 650 °C, duration 30 s
Warranty period	5 years
Lighting Technology	LED

ENEC mark	ENEC mark
EU RoHS compliant	Yes
Application Conditions	
Maximum dim level	Not applicable
Performance ambient temperature Tq	35 °C
Suitable for random switching	Yes
Light Technical	
Luminous Flux	10,500 lumen

CoreLine Highbay Gen5

Saturated Red (R9)	<50
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	157 lm/W
Color rendering index (CRI)	>80
Flickering value (PstLM)	0.5
Stroboscopic effect value (SVM)	1
Light source color	865 cool daylight
Optic type	Narrow beam
Luminaire light beam spread	55°
Unified glare rating CEN	22

Operating and Electrical

Line Frequency	50 or 60 Hz
Input Voltage	220 to 240 V
Inrush current	40 A
Inrush time	600 ms
Power Consumption	67 W
Power Factor (Fraction)	0.95
Connection	Connection unit 3-pole
Cable	Cable 0.3 m with connector 3-pole
Number of products on MCB of 16 A type B	6

Temperature

Ambient temperature range	-30 to +50 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum die-cast
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	-
Housing Color	Gray
Optical cover/lens finish	Clear
Overall length	290 mm
Overall height	90 mm

Overall diameter	290 mm
------------------	--------

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Sustainability rating	-
Protection class IEC	Safety class I
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	18.2 m

Initial Performance (IEC Compliant)

Initial chromaticity	(0.316, 0.332) SDCM<5
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life	5 %
50000 h	
Control gear failure rate at median useful life	10 %
100000 h	
Lumen maintenance at median useful life*	L85
50000 h	
Lumen maintenance at median useful life*	L75
100000 h	

Product Data

Full product code	871951495574500
Order product name	BY120P G5 LED105S/865 PSU NB
EAN/UPC - Product	8719514955745
Order code	911401630008
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401630008
Full product name	BY120P G5 LED105S/865 PSU NB
EAN/UPC - Case	8719514955745

CoreLine Highbay Gen5

Dimensional drawing

