

Lighting

PHILIPS

CoreLine Highbay Gen5

BY122P G5 LED250S/840 PSD WB

CoreLine Highbay Gen5, 168 W, 25000 lumen, 4000 K, DALI, Wide beam, IP65, IK08

CoreLine Highbay Gen5 delivers on the CoreLine promise of innovative, easy-to-use and high-quality luminaires. A reliable, highly-efficient luminaire with a very longlifetime, it delivers great energy savings and requires less maintenance. At the same time, CoreLine Highbay is very easy to handle. The luminaire can be installed on your existing grid and the electrical connection is a straightforward task, with no need to open the luminaire and an external IP65 connector. With a choice of two beam angles: narrow and wide beam, you can adjust your lighting plan to suit your exact needs. This range also includes Interact Ready luminaires with integrated wireless communications and integrated movement and daylight sensors. So CoreLine Highbay Gen5 is ready to be used with any Interact connected lighting system.

Product data

General Information	
Light source replaceable	No
CE mark	Yes
Number of gear units	2 units
Driver included	Yes
El a servicia la dista con en el c	
Flammability mark	For mounting on normally flammable
Flammability mark	For mounting on normally flammable surfaces
Glow-wire test	с ,
	surfaces
Glow-wire test	surfaces Temperature 650 °C, duration 30 s

ENEC mark	ENEC mark
EU RoHS compliant	Yes
Application Conditions	
Maximum dim level	20%
Performance ambient temperature Tq	35 ℃
Suitable for random switching	Yes
Light Technical	
Luminous Flux	25,000 lumen


CoreLine Highbay Gen5

Contractor of Dovel (DO)	
Saturated Red (R9)	<50
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	149 lm/W
Color rendering index (CRI)	>80
Flickering value (PstLM)	0.5
Stroboscopic effect value (SVM)	1
Light source color	840 neutral white
Optic type	Wide beam
Luminaire light beam spread	85° × 85°
Unified glare rating CEN	25
Operating and Electrical	
Line Frequency	50 or 60 Hz
Input Voltage	220 to 240 V
Inrush current	60 A
Inrush time	600 ms
Power Consumption	168 W
Power Factor (Fraction)	0.95
Connection	Connection unit 3-pole
Cable	Cable 0.3 m with connector 3-pole
Number of products on MCB of 16 A type B	6
Temperature	
Temperature Ambient temperature range	-30 to +50 °C
	-30 to +50 °C
	-30 to +50 °C
Ambient temperature range	-30 to +50 °C Yes
Ambient temperature range Controls and Dimming	
Ambient temperature range Controls and Dimming Dimmable	Yes
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer	Yes Power supply unit with DALI interface
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface	Yes Power supply unit with DALI interface DALI
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface	Yes Power supply unit with DALI interface DALI
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output	Yes Power supply unit with DALI interface DALI
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output Mechanical and Housing	Yes Power supply unit with DALI interface DALI No
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output Mechanical and Housing Housing Material	Yes Power supply unit with DALI interface DALI No
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output Mechanical and Housing Housing Material Reflector material	Yes Power supply unit with DALI interface DALI No Aluminum die-cast -
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output Mechanical and Housing Housing Material Reflector material Optic material	Yes Power supply unit with DALI interface DALI No Aluminum die-cast - Polycarbonate
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output Mechanical and Housing Housing Material Reflector material Optic material Optical cover/lens material	Yes Power supply unit with DALI interface DALI No Aluminum die-cast - Polycarbonate
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output Mechanical and Housing Housing Material Reflector material Optic material Optical cover/lens material Fixation material	Yes Power supply unit with DALI interface DALI No Aluminum die-cast - Polycarbonate Polycarbonate -
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output Mechanical and Housing Housing Material Reflector material Optic material Optical cover/lens material Fixation material Housing Color	Yes Power supply unit with DALI interface DALI No Aluminum die-cast - Polycarbonate Polycarbonate - Gray

Overall height	126 mm
Overall diameter	393 mm
Approval and Application	
	IDCC (Duct persetuation, pusheated int
Ingress protection code	IP65 [Dust penetration-protected, jet-
	proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Sustainability rating	-
Protection class IEC	Safety class I
Photobiological risk	Photobiological risk group 1@200mm to
	EN62778
Photobiological risk specification	18.2 m
Initial Performance (IEC Compliant)	
Initial Performance (IEC Compliant) Initial chromaticity	(0.385, 0.380) SDCM<5
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life	5 %
Control gear failure rate at median useful life 50000 h	5%
-	5 %
50000 h	
50000 h Control gear failure rate at median useful life	
50000 h Control gear failure rate at median useful life 100000 h	10 %
50000 h Control gear failure rate at median useful life 100000 h Lumen maintenance at median useful life*	10 %
50000 h Control gear failure rate at median useful life 100000 h Lumen maintenance at median useful life* 50000 h	10 % L85
50000 h Control gear failure rate at median useful life 100000 h Lumen maintenance at median useful life* 50000 h Lumen maintenance at median useful life* 100000 h	10 % L85
50000 h Control gear failure rate at median useful life 100000 h Lumen maintenance at median useful life* 50000 h Lumen maintenance at median useful life*	10 % L85
50000 h Control gear failure rate at median useful life 100000 h Lumen maintenance at median useful life* 50000 h Lumen maintenance at median useful life* 100000 h	10 % L85
50000 h Control gear failure rate at median useful life 100000 h Lumen maintenance at median useful life* 50000 h Lumen maintenance at median useful life* 100000 h Product Data	10 % L85 L75
50000 h Control gear failure rate at median useful life 100000 h Lumen maintenance at median useful life* 50000 h Lumen maintenance at median useful life* 100000 h Product Data Full product code	10 % L85 L75 871951495587500
50000 h Control gear failure rate at median useful life 100000 h Lumen maintenance at median useful life* 50000 h Lumen maintenance at median useful life* 100000 h Product Data Full product code Order product name	10 % L85 L75 871951495587500 BY122P G5 LED250S/840 PSD WB
50000 h Control gear failure rate at median useful life 100000 h Lumen maintenance at median useful life* 50000 h Lumen maintenance at median useful life* 100000 h Product Data Full product code Order product name EAN/UPC - Product	10 % L85 L75 871951495587500 BY122P G5 LED250S/840 PSD WB 8719514955875
50000 h Control gear failure rate at median useful life 100000 h Lumen maintenance at median useful life* 50000 h Lumen maintenance at median useful life* 100000 h Product Data Full product code Order product name EAN/UPC - Product Order code	10 % L85 L75 871951495587500 BY122P G5 LED250S/840 PSD WB 8719514955875 911401631308
50000 h Control gear failure rate at median useful life 100000 h Lumen maintenance at median useful life* 50000 h Lumen maintenance at median useful life* 100000 h Product Data Full product code Order product name EAN/UPC - Product Order code Numerator - Quantity Per Pack	10 % L85 L75 871951495587500 BY122P G5 LED250S/840 PSD WB 8719514955875 911401631308 1
50000 h Control gear failure rate at median useful life 100000 h Lumen maintenance at median useful life* 50000 h Lumen maintenance at median useful life* 100000 h Product Data Full product code Order product name EAN/UPC - Product Order code Numerator - Quantity Per Pack Numerator - Packs per outer box	10 % L85 L75 871951495587500 BY122P G5 LED250S/840 PSD WB 8719514955875 911401631308 1 1

CoreLine Highbay Gen5

Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, September 5 - data subject to change