



# CoreLine Highbay Gen5

## BY122P G5 LED300S/840 PSD WB

CoreLine Highbay Gen5, 205 W, 30000 lumen, 4000 K, DALI, Wide beam, IP65, IK08

CoreLine Highbay Gen5 delivers on the CoreLine promise of innovative, easy-to-use and high-quality luminaires. A reliable, highly-efficient luminaire with a very long-lifetime, it delivers great energy savings and requires less maintenance. At the same time, CoreLine Highbay is very easy to handle. The luminaire can be installed on your existing grid and the electrical connection is a straightforward task, with no need to open the luminaire and an external IP65 connector. With a choice of two beam angles: narrow and wide beam, you can adjust your lighting plan to suit your exact needs. This range also includes Interact Ready luminaires with integrated wireless communications and integrated movement and daylight sensors. So CoreLine Highbay Gen5 is ready to be used with any Interact connected lighting system.

### Product data

General Information		Application Conditions	
Light source replaceable	No	ENEC mark	ENEC mark
CE mark	Yes	EU RoHS compliant	Yes
Number of gear units	2 units	Maximum dim level	13%
Driver included	Yes	Performance ambient temperature Tq	35 °C
Flammability mark	For mounting on normally flammable surfaces	Suitable for random switching	Yes
Glow-wire test	Temperature 650 °C, duration 30 s		
Warranty period	5 years		
Lighting Technology	LED		
		Light Technical	
		Luminous Flux	30,000 lumen

# CoreLine Highbay Gen5

Saturated Red (R9)	<50
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	146 lm/W
Color rendering index (CRI)	>80
Flickering value (PstLM)	0.5
Stroboscopic effect value (SVM)	1
Light source color	840 neutral white
Optic type	Wide beam
Luminaire light beam spread	85° x 85°
Unified glare rating CEN	25

## Operating and Electrical

Line Frequency	50 or 60 Hz
Input Voltage	220 to 240 V
Inrush current	60 A
Inrush time	600 ms
Power Consumption	205 W
Power Factor (Fraction)	0.95
Connection	Connection unit 3-pole
Cable	Cable 0.3 m with connector 3-pole
Number of products on MCB of 16 A type B	6

## Temperature

Ambient temperature range	-30 to +50 °C
---------------------------	---------------

## Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI interface
Control interface	DALI
Constant light output	No

## Mechanical and Housing

Housing Material	Aluminum die-cast
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	-
Housing Color	Gray
Optical cover/lens finish	Clear
Overall height	126 mm

Overall diameter	393 mm
------------------	--------

## Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Sustainability rating	-
Protection class IEC	Safety class I
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	18.2 m

## Initial Performance (IEC Compliant)

Initial chromaticity	(0.385, 0.380) SDCM<5
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

## Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 50000 h	L85
Lumen maintenance at median useful life* 100000 h	L75

## Product Data

Full product code	871951495603200
Order product name	BY122P G5 LED300S/840 PSD WB
EAN/UPC - Product	8719514956032
Order code	911401632908
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401632908
Full product name	BY122P G5 LED300S/840 PSD WB
EAN/UPC - Case	8719514956032

# CoreLine Highbay Gen5

## Dimensional drawing

