



CoreLine Trunking Gen2

LL234X 80S/840 1x PSU HB NB 5x1.5

LL234X | Coreline Trunking Gen2 – Power supply unit (ON/OFF)
– Narrow beam – 35° x 71°

CoreLine Trunking Gen2 is a light-line system that is designed for simplicity. It comes in a choice of lengths, flux packages and beam shapes to suit every project and application. Easy to use and integrate with spots and sensors, CoreLine Trunking Gen2 provides consistent, high-quality lighting with added protection against accidental water ingress. The innovative system is also easy to assemble and install for faster retrofits and refurbishments.

Product data

General Information	
Light source replaceable	No
CE mark	Yes
Number of gear units	1 unit
Driver included	Yes
Flammability mark	-
Glow-wire test	Temperature 850 °C, duration 30 s
Warranty period	5 years
Service tag	Yes
Product family code	LL234X [Coreline Trunking Gen2]
Lighting Technology	LED
ENEC mark	ENEC plus mark
EU RoHS compliant	Yes
Value ladder	Value

Application Conditions	
Maximum dim level	Not applicable
Performance ambient temperature Tq	25 °C
Suitable for random switching	Yes
Light Technical	
Luminous Flux	8,000 lumen
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	157 lm/W
Color rendering index (CRI)	>80
Beam angle of light source	120 degree(s)
Light source color	840 neutral white
Optic type	Narrow beam
Luminaire light beam spread	35° x 71°

CoreLine Trunking Gen2

Unified glare rating CEN	19
--------------------------	----

Operating and Electrical

Line Frequency	50 to 60 Hz
Input Voltage	220 to 240 V
Initial CLO power consumption	- W
Average CLO power consumption	- W
Inrush current	19 A
Inrush time	0.280 ms
Power Consumption	51 W
Power Factor (Fraction)	0.95
Connection	Connection unit 5-pole
Cable	-
Number of products on MCB of 16 A type B	24

Temperature

Ambient temperature range	-20 to +35 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No

Mechanical and Housing

Housing Material	Steel
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Housing Color	White RAL9016
Optical cover/lens finish	Frosted
Overall length	3,400 mm
Overall width	80 mm
Overall height	50 mm

Dimensions (Height x Width x Depth)	50 x 80 x 3400 mm
-------------------------------------	-------------------

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Sustainability rating	-
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Initial chromaticity	(0.38, 0.38) SDCM <3
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%


Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life	5 %
50000 h	
Control gear failure rate at median useful life	0.1 %
100000 h	
Lumen maintenance at median useful life* 50000 h	L85
Lumen maintenance at median useful life* 100000 h	L75

Product Data

Full product code	871951463373500
Order product name	LL234X 80S/840 1x PSU HB NB 5x1.5
Order code	910925868825
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	910925868825
Full product name	LL234X 80S/840 1x PSU HB NB 5x1.5
EAN/UPC - Case	8719514633735

Dimensional drawing



CoreLine Trunking Gen2

