



CoreLine Trunking Gen2

LL234X 90S/840 2x PSU WB 5x1.5

Coreline Trunking Gen2, 56 W, Power supply unit (On/Off), Wide beam, 84° x 84°

CoreLine Trunking Gen2 is a light-line system that is designed for simplicity. It comes in a choice of lengths, flux packages and beam shapes to suit every project and application. Easy to use and integrate with spots and sensors, CoreLine Trunking Gen2 provides consistent, high-quality lighting with added protection against accidental water ingress. The innovative system is also easy to assemble and install for faster retrofits and refurbishments.

Product data

General Information		Application Conditions	
Light source replaceable	No	Maximum dim level	Not applicable
CE mark	Yes	Performance ambient temperature Tq	25 °C
Number of gear units	2 units	Suitable for random switching	Yes
Driver included	Yes		
Flammability mark	-	Light Technical	
Glow-wire test	Temperature 850 °C, duration 30 s	Luminous Flux	9,000 lumen
Warranty period	5 years	Correlated Color Temperature (Nom)	4000 K
Service tag	Yes	Luminous Efficacy (rated) (Nom)	161 lm/W
Product family code	LL234X [Coreline Trunking Gen2]	Color rendering index (CRI)	>80
Lighting Technology	LED	Beam angle of light source	120 degree(s)
ENEC mark	ENEC plus mark	Light source color	840 neutral white
EU RoHS compliant	Yes	Optic type	Wide beam
Value ladder	Value	Luminaire light beam spread	84° x 84°

CoreLine Trunking Gen2

Unified glare rating CEN	19
--------------------------	----

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Voltage	220 to 240 V
Initial CLO power consumption	- W
Average CLO power consumption	- W
Inrush current	38 A
Inrush time	0.280 ms
Power Consumption	56 W
Power Factor (Fraction)	0.95
Connection	Connection unit 5-pole
Cable	-
Number of products on MCB of 16 A type B	12

Temperature	
Ambient temperature range	-20 to +35 °C

Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No

Mechanical and Housing	
Housing Material	Steel
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Housing Color	White RAL9016
Optical cover/lens finish	Frosted
Overall length	3,400 mm
Overall width	80 mm

Overall height	50 mm
Dimensions (Height x Width x Depth)	50 x 80 x 3400 mm


Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Sustainability rating	-
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)	
Initial chromaticity	(0.38, 0.38) SDCM <3
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 50000 h	5 %
Control gear failure rate at median useful life 100000 h	0.1 %
Lumen maintenance at median useful life* 50000 h	L85
Lumen maintenance at median useful life* 100000 h	L75

Product Data	
Full product code	871951461792600
Order product name	LL234X 90S/840 2x PSU WB 5x1.5
Order code	910925868232
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	910925868232
Full product name	LL234X 90S/840 2x PSU WB 5x1.5
EAN/UPC - Case	8719514617926

Dimensional drawing



CoreLine Trunking Gen2

