



CoreLine Trunking Gen2

LL200Z MB-SW 2xEP CU7 WH

Coreline Trunking Gen2, Finger-protected, 0.2 J standard, White

CoreLine Trunking Gen2 is a light-line system that is designed for simplicity. It comes in a choice of lengths, flux packages and beam shapes to suit every project and application. Easy to use and integrate with spots and sensors, CoreLine Trunking Gen2 provides consistent, high-quality lighting with added protection against accidental water ingress. The innovative system is also easy to assemble and install for faster retrofits and refurbishments.

Product data

General Information	
Angle	-
Accessory color	White
Product family code	LL200Z [Coreline Trunking Gen2]
Value ladder	Value
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Voltage	220 to 240 V
Mechanical and Housing	
Overall length	267 mm
Overall width	80 mm
Overall height	50 mm
Dimensions (Height x Width x Depth)	50 x 80 x 267 mm

Material	Steel
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I
Product Data	
Full product code	871951410819600
Order product name	LL200Z MB-SW 2xEP CU7 WH
Order code	910925867562
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	910925867562
Full product name	LL200Z MB-SW 2xEP CU7 WH
EAN/UPC - Case	8719514108196

CoreLine Trunking Gen2

EAN/UPC - Product/Case	8719514108196
------------------------	---------------

Dimensional drawing

