



CoreLine Trunking Gen2

LL217X 7x1.5 BC

Coreline Trunking Gen2

CoreLine Trunking Gen2 is a light-line system that is designed for simplicity. It comes in a choice of lengths, flux packages and beam shapes to suit every project and application. Easy to use and integrate with spots and sensors, CoreLine Trunking Gen2 provides consistent, high-quality lighting with added protection against accidental water ingress. The innovative system is also easy to assemble and install for faster retrofits and refurbishments.

Product data

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Voltage	220 to 240 V
General Information	
Accessory color	White
Product family code	LL217X [Coreline Trunking Gen2]
Value ladder	Value
Mechanical and Housing	
Overall length	1,700 mm
Overall width	80 mm
Overall height	50 mm
Dimensions (Height x Width x Depth)	50 x 80 x 1700 mm
Material	Steel

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I
Product Data	
Full product code	871951410846200
Order product name	LL217X 7x1.5 BC
Order code	910925867589
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	910925867589
Full product name	LL217X 7x1.5 BC
EAN/UPC - Case	8719514108462

CoreLine Trunking Gen2

Dimensional drawing

