



LuxSpace PoE

DN572B LED24S/830 POE-E C WH

LuxSpace PoE, 20 W, 200x200 mm, 2600 lumen, 3000 K, Power over Ethernet, UGR19, High-gloss reflector, IP20

With Power-over-Ethernet (PoE) technology, LuxSpace PoE receives power and data over a single standard Ethernet cable, eliminating the need for separate power cabling. With the simple click of a connector, LuxSpace PoE luminaires become part of a complete, integrated connected lighting system, delivering extraordinary illumination experiences and value beyond illumination. A built-in lighting and control system gives office users personal control over their preferred light settings via a specially designed smartphone app. With integrated sensors, LuxSpace PoE luminaires can track activity patterns, daylight levels, and in the near future humidity, CO2, temperature, or other data. This data allows facility managers to gain deep insight into building operations, helping them optimize the delivery of resources, enhance the experience and performance of occupants, and support improved asset management.

Product data

General Information		Flammability mark	
Light source replaceable	No	For mounting on normally flammable surfaces	
Number of gear units	1 unit	ENEC mark	
Driver included	Yes	-	
Service tag	Yes	Glow-wire test	
Product family code	DN572B [LuxSpace2 Square]	Temperature 850 °C, duration 5 s	
Lighting Technology	LED	EU RoHS compliant	
Value ladder	Specification	Yes	
CE mark	Yes	Light Technical	
Warranty period	5 years	Luminous Flux	
		2,600 lumen	
		Correlated Color Temperature (Nom)	
		3000 K	
		Luminous Efficacy (rated) (Nom)	
		130 lm/W	
		Color rendering index (CRI)	
		>80	

Light source color	830 warm white
Optic type	-
Luminaire light beam spread	80°
Unified glare rating CEN	19

Operating and Electrical

Line Frequency	50 to 60 Hz
Input Voltage	48 to 54 V
Inrush current	16 A
Inrush time	0.195 ms
Power Consumption	20 W
Power Factor (Fraction)	0.9
Connection	Push-in connector and pull relief
Cable	-
Number of products on MCB of 16 A type B	24

Temperature

Ambient temperature range	+10 to +25 °C
---------------------------	---------------

Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Luminaire controller with power over Ethernet
Control interface	Power over Ethernet
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum die cast
Reflector material	Polycarbonate aluminum coated
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Housing Color	White
Optical cover/lens finish	-
Reflector Finish	High-gloss reflector
Overall length	200 mm
Overall width	200 mm

Overall height	119 mm
Dimensions (Height x Width x Depth)	119 x 200 x 200 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Sustainability rating	-
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)

Initial chromaticity	(0.43, 0.40) SDCM <2
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L90

Application Conditions

Maximum dim level	1%
Performance ambient temperature Tq	25 °C
Suitable for random switching	Yes

Product Data

Full product code	871869997070300
Order product name	DN572B LED24S/830 POE-E C WH
Order code	910505100941
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	910505100941
Full product name	DN572B LED24S/830 POE-E C WH
EAN/UPC - Case	8718699970703
EAN/UPC - Product/Case	8718699970703

Dimensional drawing



