



Maxos fusion

LL523X LED62S/840 PSD MB 7 WH HE

LL523X | Maxos fusion Panel - 840 neutral white - Power supply unit with DALI interface - Medium beam

Maxos fusion is an adaptable LED trunking system that offers an excellent quality of light while more than halving energy costs compared to fluorescent lamps. For retail applications, a family of linear panels, non-linear modules and a spot portfolio can be smoothly integrated into the track backbone to let your merchandise sparkle and stand out. For industrial applications, the focus is on reducing installation and maintenance cost by using fewer linear panels. With the electrical set-up of up to 13 wires, the freedom to position these fixtures as required and the integration of other services/third-party hardware, the system allows you to reduce ceiling clutter. It can also be easily re-configured to accommodate future lay-out changes. The infrastructure is enabled to integrate sensors for data collection, giving you the opportunity to use insightful granular information to support your business.

Product data

General Information		EU RoHS compliant		Yes
Light source replaceable	No	Value ladder	Specification	
CE mark	Yes	Application Conditions		
Number of gear units	1 unit	Maximum dim level	1%	
Driver included	Yes	Performance ambient temperature Tq	25 °C	
Flammability mark	For mounting on normally flammable surfaces	Suitable for random switching	Not applicable	
Glow-wire test	Temperature 850 °C, duration 30 s	Light Technical		
Warranty period	5 years	Luminous Flux	6,200 lumen	
Product family code	LL523X [Maxos fusion Panel]	Correlated Color Temperature (Nom)	4000 K	
Lighting Technology	LED	Luminous Efficacy (rated) (Nom)	180 lm/W	
ENEC mark	ENEC mark			

Maxos fusion

Color rendering index (CRI)	>80
Flickering value (PstLM)	1
Stroboscopic effect value (SVM)	0.4
Beam angle of light source	120 degree(s)
Light source color	840 neutral white
Optic type	Medium beam
Luminaire light beam spread	66° x 80°
Unified glare rating CEN	25

Operating and Electrical

Line Frequency	50 to 60 Hz
Input Voltage	220-240 V
Inrush current	21 A
Inrush time	0.28 ms
Power Consumption	34.5 W
Power Factor (Fraction)	0.98
Connection	Connection unit 7-pole
Cable	-
Number of products on MCB of 16 A type B	24

Temperature

Ambient temperature range	-20 to +35 °C
---------------------------	---------------

Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI interface
Control interface	DALI
Constant light output	No

Mechanical and Housing

Housing Material	Steel
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Housing Color	White
Optical cover/lens finish	Textured

Overall length	2,276 mm
Overall width	62 mm
Overall height	14 mm
Dimensions (Height x Width x Depth)	14 x 62 x 2276 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Sustainability rating	Lighting for circularity
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Initial chromaticity	(0.34, 0.35) SDCM <3
Luminous flux tolerance	+/-7%
Power consumption tolerance	+/-11%


Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 50000 h	L95
Lumen maintenance at median useful life* 100000 h	L85

Product Data

Full product code	871951473755600
Order product name	LL523X LED62S/840 PSD MB 7 WH HE
Order code	910925868949
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	910925868949
Full product name	LL523X LED62S/840 PSD MB 7 WH HE
EAN/UPC - Case	8719514737556

Dimensional drawing



Maxos fusion

