



Maxos fusion

Luminous Efficacy (rated) (Nom)	177 lm/W
Color rendering index (CRI)	>80
Flickering value (PstLM)	1
Stroboscopic effect value (SVM)	0.4
Beam angle of light source	120 degree(s)
Light source color	840 neutral white
Optic type	Wide beam
Luminaire light beam spread	85° x 85°
Unified glare rating CEN	22

Operating and Electrical

Line Frequency	50 to 60 Hz
Input Voltage	220–240 V
Inrush current	4.5 A
Inrush time	1 ms
Power Consumption	57 W
Power Factor (Fraction)	0.97
Connection	Connection unit 7-pole
Cable	–
Number of products on MCB of 16 A type B	18

Temperature

Ambient temperature range	–20 to +35 °C
---------------------------	---------------

Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI interface
Control interface	DALI
Constant light output	No

Mechanical and Housing

Housing Material	Steel
Reflector material	–
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Housing Color	White
Optical cover/lens finish	Textured

Overall length	2,276 mm
Overall width	62 mm
Overall height	14 mm
Dimensions (Height x Width x Depth)	14 x 62 x 2276 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Sustainability rating	Lighting for circularity
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Initial chromaticity	(0.34, 0.35) SDCM <3
Luminous flux tolerance	+/-7%
Power consumption tolerance	+/-11%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life	5 %
50000 h	
Control gear failure rate at median useful life	10 %
100000 h	
Lumen maintenance at median useful life*	L95
50000 h	
Lumen maintenance at median useful life*	L85
100000 h	

Product Data

Full product code	871951473774700
Order product name	LL523X LED100S/840 SIA WB 7 WH HE
Order code	910925868968
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	910925868968
Full product name	LL523X LED100S/840 SIA WB 7 WH HE
EAN/UPC - Case	8719514737747

Dimensional drawing



