



# UV-C disinfection upper air wall mounted

#### WL346W 1xTUV T5 25W HFS

PHILIPS UV-C DISINFECTION UPPER AIR, 1, HF Selectalume, White and black, 29.6~W, 230~V

As part of the Philips UV-C disinfection upper air device series, Philips UV-C disinfection upper air wall mounted is designed to be installed on walls for the disinfection of air in a wide range of applications. Optimized for low ceiling heights, the UV-C rays are distributed at device level and above. The beam of UV-C rays is controlled by specific reflectors and the louvre design. This allows for the disinfection of the air in a space, while ensuring that day-to-day business activities can continue underneath the area where the device is active.

#### **Warnings and Safety**

- DANGER: Risk Group 3 UV product. Like any disinfection system, UV-C lamps and devices must be installed and used in the correct way. Direct exposure to UV-C can be dangerous and result in a sunburn-like reaction to the skin and serious damage to the cornea. As UV-C is invisible to the eye, the UV-C upper air device must be installed together with adequate safeguards to ensure that the UV-C upper air device can be operated in a safe way. The UV-C upper air device are only to be used as components in a system that consists of adequate safety safeguards such as, but not limited to, those indicated in the mounting instructions and/or user manuals. Direct exposure to UV-C is dangerous. Philips UV-C luminaires systems must only be sold through qualified partners and installed by professionals according to our stringent safety and legal requirements. Our UV-C products are not meant to be used in applications or activities which may cause and/or lead to death, personal injury and/or damage to the environment.
- [1] According to results obtained from a laboratory test conducted by Innovative Bioanalysis, a CAP, CLIA, AABB Certified Safety Reference Laboratory, in a room with sufficient air circulation. For more information, please refer to the test report available in the "related tools" part of this webpage

Datasheet, 2023, September 25 data subject to change

# UV-C disinfection upper air wall mounted


## **Product data**

Concept Information	
General Information  Number of gear units	1 unit
Gear	HF-S [HF Selectalume]
Product family code	WL345W [PHILIPS UV-C DISINFECTION
	UPPER AIR]
CE mark	Yes
Warranty period	1 years
Flammability mark	-
ENEC mark	-
Glow-wire test	Temperature 650 °C, duration 30 s
EU RoHS compliant	Yes
Light Tochnical	
Light Technical	1
Number of light sources	1
Beam angle of light source	- degree(s)
Optic type	Lamellae louver
Luminaire light beam spread	-
Operating and Electrical	
Operating and Electrical	220 V
Input Voltage	230 V
Line Frequency	50 Hz
Inrush current	18 A
Inrush time	0.35 ms
Power Consumption	29.6 W
Power Factor (Fraction)	0.98
Connection	Push-in connector 3-pole
Cable	-
Number of products on MCB of 16 A type B	28
Temperature	
	+10 to +40 °C
Ambient temperature range	-10 to +40 C
Controls and Dimming	
Dimmable	No
Control interface	-
Mechanical and Housing	
Housing Material	Aluminum
Reflector material	Aluminum
	Aluminum

Housing Color	White and black
Mounting device	Wall-mounting bracket
Overall length	553 mm
Overall width	185 mm
Overall height	140 mm
Dimensions (Height x Width x Depth)	140 x 185 x 553 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Sustainability rating	-
Protection class IEC	Safety class I
Photobiological risk	Photobiological risk group 3 @200mm to
	EN62778
UV	
UV-C radiation	0.53 W
UV-C irradiance defined at 2m	972 mW/m²
UV-C irradiance defined at 0.2m	8,060 mW/m²
Initial Performance (IEC Compliant)	
Power consumption tolerance	+/-10%
Application Conditions	
Maximum dim level	Not applicable
Performance ambient temperature Tq	25 ℃
Suitable for random switching	No
Product Data	
Full product code	871016366504700
Order product name	WL346W 1xTUV T5 25W HFS
Order code	919206000111
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	919206000111
Full product name	WL346W 1xTUV T5 25W HFS
EAN/UPC - Case	8710163665047
EAN/UPC - Product/Case	8710163665047

# UV-C disinfection upper air wall mounted

## Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.