





MASTER UltraEfficient LED bulb

MAS LEDBulb D 4-60W E27 827 A60 CL G UE

This is the most efficient LED bulb from Philips brand. 210lm/W helps to concrete the company statement of sustainability. 50000 hour lifetime helps to extend the replacement cycle to reduce the waste. This is not only the high SPEC product, but also keep the light quality of Philips brand

Product data

General Information	
Cap-Base	E27 [E27]
Nominal lifetime	50,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
EU RoHS compliant	Yes
Light Technical	
Color Code	827 [CCT of 2700K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	840 lumen
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	210 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %


Stroboscopic effect value (SVM)	0.4
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	4 W
Lamp Current (Nom)	23 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.85
Voltage (Nom)	220-240 V
Voltage (Nom)	220 V
Temperature	
Ambient temperature range	-20 to +45 °C
T-Case Maximum (Nom)	70 °C

MASTER UltraEfficient LED bulb


Controls and Dimming		
Dimmable	Only with specific dimmers	
Mechanical and Housing		
Bulb Finish	Clear	
Bulb Material	Glass	
Bulb Shape	A60 [A 60mm]	
Approval and Application		
Energy Efficiency Class	A	
Energy Consumption kWh/1000 h	4 kWh	
EPREL Registration Number	1618549	
EyeComfort	Yes	

Product Data	
Full product code	872016924864900
Order product name	MAS LEDBulb D 4-60W E27 827 A60 CL G UE
Order code	929003691502
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929003691502
Full product name	MAS LEDBulb D 4-60W E27 827 A60 CL G UE
EAN/UPC - Case	8720169248656
EAN/UPC - Product/Case	8720169248649

Dimensional drawing




Photometric data



Spectral Power Distribution Colour - MAS LEDBulb D 4-60W E27 827 A60 CL G UE




MAS LEDBulb D 4-60W E27 827 A60 CL G UE



Light Distribution Diagram - MAS LEDBulb D 4-60W E27 827 A60 CL G UE


MASTER UltraEfficient LED bulb

Photometric data




General uniform lighting - MAS LEDBulb D 4-60W E27 827 A60 CL G UE

Lifetime







Lumen Maintenance Diagram - MAS LEDBulb D 4-60W E27 827 A60 CL G UE



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.