PHILIPS Lighting



3-circuit Square RCS750

RBS750 3C L2000 WH (XTSF4200-3)

3-circuit Square RCS750, Normal, White, Tool-protected

The RCS750 3-circuit square track system is made up of a solid aluminum track available in lengths of 1, 2, 3 and 4 m with four electrical conductors. Any given configuration can be created easily: horizontal or vertical, mounted on or in the ceiling, on the wall or on free-standing panels. The system can also be used as a floating structure. All luminaires have a separate power supply and can be switched selectively. They can be moved easily to change the lighting and presentation. In this way, a multifunctional track system can be created for accent lighting as well as for suspending advertising and decorative material. A range of adaptors, power supply connections and mounting accessories is also available


Product data

General Information	
Accessory color	White
Glow-wire test	Temperature 850 °C, duration 5 s
Mechanical and Housing	
Overall length	2,000 mm
Approval and Application	
Ingress protection code	IP30 [Tool-protected]
Protection class IEC	Safety class I
Product Data	
Order product name	RBS750 3C L2000 WH (XTSF4200-3)

Full product name	RBS750 3C L2000 WH (XTSF4200-3)
Full product code	871155914980600
Order code	910930009118
Material Nr. (12NC)	910930009118
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711559149806
Numerator - Packs per outer box	1
EAN/UPC - Case	8711559149806

3-circuit Square RCS750

Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, October 30 - data subject to change