



Ledinaire Wall-mounted WL060V

WL060V LED11S/840 PSU II WH

Ledinaire Wall-mounted WL060V, 11 W, D285 mm, 1100 lm, 4000 K, IP44

The Philips Ledinaire wall-mounted family has a reputation for simply great LED. The popular, off-the-shelf LED luminaires in this range promise high Philips quality levels at a very competitive price. Reliable, energy-efficient and affordable, Ledinaire WL060V wall-mounted luminaires are designed to cover a wide range of indoor applications from corridors to public entrances. The modern, unobtrusive design also comes in a choice of two sizes and lumen packages, so you can create a uniform look and feel everywhere you need wall-mounted LEDs.

Product data

General Information		Light Technical	
Light source replaceable	No	Luminous Flux	1,100 lm
Number of gear units	1 unit	Saturated Red (R9)	<50
Driver included	Yes	Correlated Color Temperature (Nom)	4000 K
Lighting Technology	LED	Luminous Efficacy (rated) (Nom)	100 lm/W
Value ladder	Value	Color rendering index (CRI)	>80
CE mark	Yes	Flickering value (PstLM)	1
Warranty period	3 years	Stroboscopic effect value (SVM)	0.4
Flammability mark	For mounting on normally flammable surfaces	Beam angle of light source	- degree(s)
ENEC mark	ENEC mark	Light source color	840 neutral white
Glow-wire test	Temperature 650 °C, duration 30 s	Optic type	Beam angle 120°
EU RoHS compliant	Yes	Luminaire light beam spread	120°
		Unified glare rating CEN	22

Ledinaire Wall-mounted WL060V

Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 or 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	- W
Inrush current	10 A
Inrush time	0.0019 ms
Power Consumption	11 W
Power Factor (Fraction)	0.9
Connection	Push-in connector 2-pole
Cable	-
Number of products on MCB of 16 A type B	35
Temperature	
Ambient temperature range	-20 to +40 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No
Mechanical and Housing	
Housing Material	Polycarbonate
Reflector material	Acrylate
Optic material	Acrylate
Optical cover material	Acrylate
Fixation material	-
Housing Color	White
Optical cover finish	Opal
Overall height	88 mm
Overall diameter	285 mm
Approval and Application	
Ingress protection code	IP44 [Wire-protected, splash-proof]
Mech. impact protection code	IK03 [0.3 J]
Sustainability rating	-
Protection class IEC	Safety class II
Photobiological risk	Photobiological risk group 0 @200mm to EN62778
Photobiological risk specification	0.2 m
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38, 0.38) SDCM≤3
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life	7.5 %
50000 h	
Lumen maintenance at median useful life*	-
35000 h	
Lumen maintenance at median useful life*	70
50000 h	
Lumen maintenance at median useful life*	-
75000 h	
Lumen maintenance at median useful life*	-
100000 h	
Application Conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Not applicable
Product Data	
Order product name	WL060V LED11S/840 PSU II WH
Full product name	WL060V LED11S/840 PSU II WH
Full product code	871951496010799
Order code	911401887484
Material Nr. (12NC)	911401887484
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514960107
Numerator - Packs per outer box	5
EAN/UPC - Case	8719514960145

Ledinaire Wall-mounted WL060V

Dimensional drawing

