



CoreLine panel

RC133V G5 34S/830 PSED W62L62 OC

CoreLine panel, 30 W, 620x620 mm, 3400 lm, 3000 K, DALI, UGR19, EL-DC

Philips CoreLine panel Gen5 delivers on the CoreLine promise of innovation, easy installation and excellent illumination. Designed as a direct replacement for functional luminaires in general lighting applications, this LED panel light's innovative MultiLumen feature offers a choice of three lumen packages in a single luminaire. This makes it easy to select the right product, gives you the flexibility respond to customer preferences on site, and means fewer product codes on stock. Installing this CoreLine RC132V LED panel is quick and easy too, thanks to a quick connector or Wieland connector. Interact Ready luminaires with integrated wireless communications are also available in this CoreLine range, ready to be used with Interact gateways, sensors and software.

Product data

General Information		EU RoHS compliant	
Light source replaceable	No	Yes	
Number of gear units	1 unit		
Driver included	Yes		
Product family code	RC133V [CORELINE PANEL]		
Lighting Technology	LED		
Value ladder	Performance		
CE mark	Yes		
Warranty period	5 years		
Flammability mark	For mounting on normally flammable surfaces		
ENEC mark	ENEC mark		
Glow-wire test	Temperature 650 °C, duration 30 s		
Light Technical			
Luminous Flux	3,400 lm		
Saturated Red (R9)	<50		
Correlated Color Temperature (Nom)	3000 K		
Luminous Efficacy (rated) (Nom)	113 lm/W		
Color rendering index (CRI)	≥80		
Flickering value (PstLM)	1		
Stroboscopic effect value (SVM)	0.4		
Light source color	830 warm white		
Optic type	Beam angle 90°		
Luminaire light beam spread	90°		

CoreLine panel

Unified glare rating CEN	19
Operating and Electrical	
Input Voltage	220–240 V
Line Frequency	50 or 60 Hz
Inrush current	20.4 A
Inrush time	195 ms
Power Consumption	30 W
Power Factor (Fraction)	0.9
Connection	Push-in connector 5-pole
Cable	-
Number of products on MCB of 16 A type B	24
Temperature	
Ambient temperature range	0 to +35 °C
Controls and Dimming	
Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI interface, DC compatible for central emergency lighting (integrated)
Control interface	DALI
Constant light output	No
Mechanical and Housing	
Housing Material	Steel
Reflector material	Acrylate
Optic material	Polystyrene
Optical cover material	Acrylate
Fixation material	-
Housing Color	White
Optical cover finish	Opal
Overall length	620 mm
Overall width	620 mm
Overall height	73 mm
Dimensions (Height x Width x Depth)	73 x 620 x 620 mm
Approval and Application	
Ingress protection code	IP20/44 [Finger-protected; wire- protected, splash-proof]

Mech. impact protection code	IK03 [0.3 J]
Sustainability rating	-
Protection class IEC	Safety class II
Photobiological risk	Photobiological risk group 0 @200mm to EN62778
Photobiological risk specification	0.2 m
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.43, 0.40) SDCM≤3
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life	5 %
50000 h	
Lumen maintenance at median useful life*	L90
50000 h	
Lumen maintenance at median useful life*	L80
100000 h	
Application Conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	3%
Suitable for random switching	Yes
Product Data	
Order product name	RC133V G5 34S/830 PSED W62L62 OC
Full product name	RC133V G5 34S/830 PSED W62L62 OC
Full product code	872016901377300
Order code	910505102357
Material Nr. (12NC)	910505102357
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169013773
Numerator - Packs per outer box	1
EAN/UPC - Case	8720169013773

CoreLine panel

Dimensional drawing

