



# CoreLine panel

## RC132V G5 36S/840 PSD W30L120 OC

CoreLine panel, 28.5 W, 1200x300 mm, 3600 lm, 4000 K, DALI, UGR19

Philips CoreLine panel Gen5 delivers on the CoreLine promise of innovation, easy installation and excellent illumination. Designed as a direct replacement for functional luminaires in general lighting applications, this LED panel light's innovative MultiLumen feature offers a choice of three lumen packages in a single luminaire. This makes it easy to select the right product, gives you the flexibility respond to customer preferences on site, and means fewer product codes on stock. Installing this CoreLine RC132V LED panel is quick and easy too, thanks to a quick connector or Wieland connector. Interact Ready luminaires with integrated wireless communications are also available in this CoreLine range, ready to be used with Interact gateways, sensors and software.

### Product data



General Information		EU RoHS compliant	
Light source replaceable	No	Yes	
Number of gear units	1 unit		
Driver included	Yes		
Lighting Technology	LED		
Value ladder	Performance		
CE mark	Yes		
Warranty period	5 years		
Flammability mark	For mounting on normally flammable surfaces		
ENEC mark	ENEC mark		
Glow-wire test	Temperature 650 °C, duration 30 s		
Light Technical			
Luminous Flux	3,600 lm		
Saturated Red (R9)	<50		
Correlated Color Temperature (Nom)	4000 K		
Luminous Efficacy (rated) (Nom)	125 lm/W		
Color rendering index (CRI)	≥80		
Flickering value (PstLM)	1		
Stroboscopic effect value (SVM)	0.4		
Light source color	840 neutral white		
Optic type	Beam angle 90°		
Luminaire light beam spread	90°		

## CoreLine panel

Unified glare rating CEN	19
<b>Operating and Electrical</b>	
Input Voltage	220-240 V
Line Frequency	50 or 60 Hz
Inrush current	18.3 A
Inrush time	0.276 ms
Power Consumption	28.5 W
Power Factor (Fraction)	0.9
Connection	Push-in connector 5-pole
Cable	-
Number of products on MCB of 16 A type B	14
<b>Temperature</b>	
Ambient temperature range	-10 to +40 °C
<b>Controls and Dimming</b>	
Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI interface
Control interface	DALI
Constant light output	No
<b>Mechanical and Housing</b>	
Housing Material	Steel
Reflector material	Acrylate
Optic material	Polystyrene
Optical cover material	Acrylate
Fixation material	-
Housing Color	White
Optical cover finish	Microprismatic lens
Overall length	1,195 mm
Overall width	295 mm
Overall height	67 mm
Dimensions (Height x Width x Depth)	67 x 295 x 1195 mm
<b>Approval and Application</b>	
Ingress protection code	IP20/44 [Finger-protected; wire-protected, splash-proof]

Mech. impact protection code	IK03 [0.3 J]
Sustainability rating	-
Protection class IEC	Safety class II
Photobiological risk	Photobiological risk group 0 @200mm to EN62778
Photobiological risk specification	0.2 m
<b>Initial Performance (IEC Compliant)</b>	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38, 0.38) SDCM≤3
Power consumption tolerance	+/-10%
<b>Over Time Performance (IEC Compliant)</b>	
Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L90
Lumen maintenance at median useful life* 100000 h	L80
<b>Application Conditions</b>	
Performance ambient temperature Tq	25 °C
Maximum dim level	3%
Suitable for random switching	Yes
<b>Product Data</b>	
Order product name	RC132V G5 36S/840 PSD W30L120 OC
Full product name	RC132V G5 36S/840 PSD W30L120 OC
Full product code	871951495013900
Order code	911401841984
Material Nr. (12NC)	911401841984
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514950139
Numerator - Packs per outer box	1
EAN/UPC - Case	8719514950139

## Dimensional drawing



## CoreLine panel

