



CoreLine panel

RC132V G5 34S/830 WIA W60L60 OC

CoreLine panel, 28.5 W, 600x600 mm, 3400 lm, 3000 K, Wireless, Interact Ready, UGR19

Philips CoreLine panel Gen5 delivers on the CoreLine promise of innovation, easy installation and excellent illumination. Designed as a direct replacement for functional luminaires in general lighting applications, this LED panel light's innovative MultiLumen feature offers a choice of three lumen packages in a single luminaire. This makes it easy to select the right product, gives you the flexibility respond to customer preferences on site, and means fewer product codes on stock. Installing this CoreLine RC132V LED panel is quick and easy too, thanks to a quick connector or Wieland connector. Interact Ready luminaires with integrated wireless communications are also available in this CoreLine range, ready to be used with Interact gateways, sensors and software.

Product data



General Information		EU RoHS compliant		Yes
Light source replaceable	No			
Number of gear units	1 unit	Light Technical		
Driver included	Yes	Luminous Flux	3,400 lm	
Connectivity	Interact Ready	Saturated Red (R9)	<50	
Lighting Technology	LED	Correlated Color Temperature (Nom)	3000 K	
Value ladder	Performance	Luminous Efficacy (rated) (Nom)	120 lm/W	
CE mark	Yes	Color rendering index (CRI)	≥80	
Warranty period	5 years	Flickering value (PstLM)	1	
Flammability mark	For mounting on normally flammable surfaces	Stroboscopic effect value (SVM)	0.4	
ENEC mark	ENEC mark	Light source color	830 warm white	
Glow-wire test	Temperature 650 °C, duration 30 s	Optic type	Beam angle 90°	
		Luminaire light beam spread	90°	

CoreLine panel

Unified glare rating CEN	19
Operating and Electrical	
Input Voltage	220–240 V
Line Frequency	50 or 60 Hz
Inrush current	4.8 A
Inrush time	0.056 ms
Power Consumption	28.5 W
Power Factor (Fraction)	0.9
Connection	Push-in connector 3-pole
Cable	–
Number of products on MCB of 16 A type B	50
Temperature	
Ambient temperature range	–10 to +40 °C
Controls and Dimming	
Dimmable	Yes
Driver/power unit/transformer	Wireless driver Interact System ready
Control interface	Wireless
Constant light output	No
Mechanical and Housing	
Housing Material	Steel
Reflector material	Acrylate
Optic material	Polystyrene
Optical cover material	Acrylate
Fixation material	–
Housing Color	White
Optical cover finish	Microprismatic lens
Overall length	595 mm
Overall width	595 mm
Overall height	70 mm
Dimensions (Height x Width x Depth)	70 x 595 x 595 mm
Approval and Application	
Ingress protection code	IP20/44 [Finger-protected; wire-protected, splash-proof]

Mech. impact protection code	IK03 [0.3 J]
Sustainability rating	–
Protection class IEC	Safety class II
Photobiological risk	Photobiological risk group 0 @200mm to EN62778
Photobiological risk specification	0.2 m
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.43, 0.40) SDCM≤3
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L90
Lumen maintenance at median useful life* 100000 h	L80
Application Conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	1%
Suitable for random switching	Yes
Product Data	
Order product name	RC132V G5 34S/830 WIA W60L60 OC
Full product name	RC132V G5 34S/830 WIA W60L60 OC
Full product code	871951495366600
Order code	911401857984
Material Nr. (12NC)	911401857984
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514953666
Numerator - Packs per outer box	1
EAN/UPC - Case	8719514953666

Dimensional drawing



CoreLine panel

