



CoreLine Waterproof

WT120C G2 LED37S/830 PSU L1200

CoreLine Waterproof, 28.5 W, L1200 mm, 3700 lm, 3000 K, Wide beam, Matte, IP65, IK08, TW1-ready

CoreLine waterproof delivers on the CoreLine promise of innovative, easy-to-use and high-quality luminaires. With its slim and stylish design, it retains the product architecture that the range is well-known and appreciated for. Installation is quick and easy, all thanks to its efficient design. CoreLine waterproof provides better wide-beam light distribution for straightforward and effective lighting. A direct replacement for traditional waterproof luminaires with fluorescent lamps ranging from 18W up to 58W, it delivers significant energy savings. Interact Ready luminaires with integrated wireless communications are also available in the CoreLine waterproof range, ready to be used with Interact connected lighting system.

Warnings and Safety

- UV radiation will damage the material over time resulting in loss of waterproof sealing and IP66 rating.
- Do not install the luminaire in locations where it will be exposed to direct sunlight.

Product data

General Information		Flammability mark	
Light source replaceable	No	ENEC mark	For mounting on easily flammable surfaces
Number of gear units	1 unit	Glow-wire test	ENEC mark
Driver included	Yes	EU RoHS compliant	Temperature 850 °C, duration 30 s
Feed-through wiring	Simple Connection and removable cover available for feed-through wiring 1-phase (internal wiring is not included)		Yes
Lighting Technology		Light Technical	
Lighting Technology	LED	Luminous Flux	3,700 lm
Value ladder	Performance	Correlated Color Temperature (Nom)	3000 K
CE mark	CE mark	Luminous Efficacy (rated) (Nom)	130 lm/W
Warranty period	5 years	Color rendering index (CRI)	>80

CoreLine Waterproof

Flickering value (PstLM)	1
Stroboscopic effect value (SVM)	1.6
Light source color	830 warm white
Optic type	Wide beam
Luminaire light beam spread	105°
Unified glare rating CEN	25

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Inrush current	14.2 A
Inrush time	0.222 ms
Power Consumption	28.5 W
Power Factor (Fraction)	0.9
Connection	Push-in connector 3-pole
Cable	-
Number of products on MCB of 16 A type B	36

Temperature

Ambient temperature range	-20 to +40 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No

Mechanical and Housing

Housing Material	Polycarbonate
Reflector material	Steel
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Stainless steel
Housing Color	Gray
Optical cover finish	Matte
Overall length	1,215 mm
Overall width	80 mm
Overall height	76 mm
Dimensions (Height x Width x Depth)	76 x 80 x 1215 mm

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Sustainability rating	-
Protection class IEC	Safety class I
Photobiological risk	Photobiological risk group 0 @200mm to EN62778

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.43,0.40)SDCM<=3
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	85
Lumen maintenance at median useful life* 100000 h	70

Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Not applicable

Product Data

Order product name	WT120C G2 LED375/830 PSU L1200
Full product name	WT120C G2 LED375/830 PSU L1200
Full product code	871016336936599
Order code	911401824681
Material Nr. (12NC)	911401824681
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163369365
Numerator - Packs per outer box	9
EAN/UPC - Case	8710163369419

CoreLine Waterproof

Dimensional drawing

