

Lok-it! HTI 700 W/60/P50

Lok-it! | HTI Short Arc Metal Halide lamps were designed as intense light sources primarily for moving head fixtures in the Entertainment marketplace.



Areas of application

- Concert lighting
- Club & Disco
- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

Product family benefits

- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency
- Rapid relamping with bayonet lock

Product family features

- Compact design and short arc gap for use in smaller and brighter fixtures
- Fast lamp replacement with one touch thanks to rotating lock
- Robust design with eXtreme Seal (XS) technology, allowing up to 450°C at the pinch seal
- Consistent lumen output over the life of the lamp
- Ceramic base allows high voltage up to 35 kV



Product datasheet

Technical data


Electrical data

Nominal wattage	700.00 W
Nominal voltage	60.0 V
Nominal current	11.70 A
Lamp current	12.0 A

Photometrical data

Nominal luminous flux	49000 lm
Color temperature	5800 K
Color rendering index Ra	75

Dimensions & weight



Diameter	25.0 mm
Length	125.0 mm
Light center length (LCL)	65.0 mm
Electrode gap cold	4.1 mm

Lifespan

Lifespan	750 h
----------	-------

Additional product data

Base (standard designation)	PGJX50
-----------------------------	--------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	29-02-2024

Product datasheet

Primary Article Identifier	4062172398909
Declaration No. in SCIP database	In work

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, Lok-it! lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172398909	Lok-it! HTI 700 W/60/P50	Shipping carton box 1	182 mm x 87 mm x 58 mm	0.92 dm ³	202.00 g
4062172398916	Lok-it! HTI 700 W/60/P50	Shipping carton box 10	312 mm x 186 mm x 194 mm	11.26 dm ³	2170.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
