



# Ledinaire High-bay

## BY030P LED150\_220\_280S/840\_50\_65 PSU WB

Ledinaire High-bay, All-in, 195 W, 100 W,  $\phi$ 320 mm, 15000 lm, 28000 lm, 4000 K, 5000 K, 6500 K, Symmetrical, IP65, IK07

The Ledinaire highbay range contains a selection of off-the-shelf highbay LED luminaires that comes with the high Philips quality levels at a competitive price. Reliable, energy efficient and affordable. Ledinaire highbay enables, simple and flexible installation, either on a hook, or optional bracket. Products can be installed with optional reflectors for lower glare.

### Product data

General Information	
Number of gear units	1 unit
Driver included	Yes
Value ladder	Value
Serviceability class	Class C, luminaire without serviceable parts, not serviceable
Warranty period	5 years
Sustainability rating	-
Light Technical	
Luminous Flux	15,000 28,000 lm
Saturated Red (R9)	<50
Correlated Color Temperature (Nom)	4000 5000 6500 K
Luminous Efficacy (rated) (Nom)	155 140 lm/W
Color rendering index (CRI)	>80
Light source color	840 neutral white, neutral white and 865 cool daylight
Optic type	Symmetrical

Luminaire light beam spread	90°
Unified glare rating CEN	31
All-in Type	All-in, Multi Lumen All-in, Multi Color Temperature
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Inrush current	68 A
Inrush time	0.213 ms
Power Consumption	195 100 W
Power Factor (Fraction)	0.9
Connection	Screw connector
Cable	Cable 0.3 m with connector 3-pole
Number of products on MCB of 16 A type B	9
Suitable for random switching	No
Protection class IEC	Safety class I


Ledinaire High-bay

Total harmonic distortion	20 %
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit
Control interface	-
Constant light output	No
Embedded control	-
Photocell	-
Mechanical and Housing	
Housing Material	Aluminum die-cast
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	-
Housing Color	Aluminum and black
Optical cover finish	Clear
Reflector Finish	-
Overall height	119 mm
Overall diameter	320 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Mounting	Suspended
Net Weight (Piece)	2.460 kg
Emergency Operation	
Central Emergency	No
Approval and Application	
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	-
Photobiological risk	Photobiological risk group 1 @200mm to EN62778

EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.9
Ambient temperature range	-30 to +50 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	-10% / +10%
Initial chromaticity	(0.38, 0.38); (0.31, 0.34) SDCM≤5
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤5
Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 50000 h	7.5 %
Control gear failure rate at median useful life 75000 h	15 %
Lumen maintenance at median useful life* 50000 h	L80
Lumen maintenance at median useful life* 75000 h	L65
Product Data	
Order product name	BY030P LED150_220_280S/840_50_65 PSU WB
Full product name	BY030P LED150_220_280S/840_50_65 PSU WB
Full product code	872016975897100
Order code	911401822687
Material Nr. (12NC)	911401822687
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169758971
Numerator - Packs per outer box	1
EAN/UPC - Case	8720169758971

Dimensional drawing

BY030P LED150\_220\_280S/840\_50\_65 PSU WB



## Ledinaire High-bay

