

# LuxSpace Mini, recessed

## DN560B LED12S/830 PSU-E C ELP3 WH

LuxSpace Mini, recessed, 13.6 W, D150 mm, 1350 lm, 3000 K, High-gloss reflector, IP20, ELP3h

Customers are looking to optimize all their resources, and that means not just their running costs (energy, etc.) but also user costs where they see much bigger impact on return. Therefore, LuxSpace is designed to provide the perfect combination of efficiency, visual comfort and design, without compromising on lighting performance (color rendering and light distribution). It offers a wide choice of options for creating the desired ambience to support user comfort, no matter the application is.

### Product data

General Information			
Light source replaceable	No	Light source color	830 warm white
Number of gear units	1 unit	Optic type	-
Driver included	Yes	Luminaire light beam spread	80°
Service tag	Yes	Unified glare rating CEN	22
Lighting Technology	LED	Operating and Electrical	
Value ladder	Specification	Input Voltage	220 to 240 V
Warranty period	5 years	Line Frequency	50 to 60 Hz
Sustainability rating	-	Inrush current	16 A
Light Technical		Inrush time	0.195 ms
Luminous Flux	1,350 lm	Power Consumption	13.6 W
Correlated Color Temperature (Nom)	3000 K	Power Factor (Fraction)	0.9
Luminous Efficacy (rated) (Nom)	99 lm/W	Connection	Push-in connector and pull relief
Color rendering index (CRI)	>80	Cable	-
		Number of products on MCB of 16 A type B	65

LuxSpace Mini, recessed

Suitable for random switching	Yes
Protection class IEC	Safety class II
Total harmonic distortion	20 %

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit external (On/Off)
Control interface	-
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum die cast
Reflector material	Polycarbonate aluminum coated
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Steel
Housing Color	White
Optical cover finish	-
Reflector Finish	High-gloss reflector
Overall height	74 mm
Overall diameter	164 mm
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Net Weight (Piece)	1.000 kg

Emergency Operation

Rated duration of the emergency lighting (when fully charged)	3 hour(s)
Emergency lighting	Emergency lighting 3 hours duration Pro version

Approval and Application

Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces

CE mark	Yes
ENEC mark	ENEC mark
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Ambient temperature range	+10 to +25 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.43, 0.40) SDCM <2
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤2


Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L90

Product Data

Order product name	DN560B LED12S/830 PSU-E C ELP3 WH
Full product name	DN560B LED12S/830 PSU-E C ELP3 WH
Full product code	871869997050500
Order code	910505100921
Material Nr. (12NC)	910505100921
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718699970505
Numerator - Packs per outer box	1
EAN/UPC - Case	8718699970505
Product family code	DN560B [LuxSpace2 Mini Low height recessed]

Dimensional drawing



## LuxSpace Mini, recessed

