



GreenSpace Accent Projector mini

ST315T LED39S/830 PSU FR24 BK

GreenSpace Accent Projector mini, Track projector, 31.5 W, 4000 lm, 3000 K, Facetted reflector with beam angle 24°, Black

The GreenSpace Accent Projector mini is the smallest size projector in the GreenSpace Accent range. With a diameter of only 80mm and integrated onboard driver, it offers a clean and small design to be discretely integrated in the store environment. The high performance and Philips Food LED recipes will deliver a strong fit to food retail and small city center store formats. The full range of beam angles and Philips Fashion LED flavors on the other hand, is creating a high quality of light to enhance the fashion collection, making this projector suitable for many different retail applications.

Warnings and Safety

- \cdot During manipulation and/or maintenance, the product has to be switched off and cooled down
- · The product must be installed out of arm's reach. Manipulating the product when hot is only possible with an insulating glove
- \cdot Luminaire should be installed and removed in accordance to the instructions in the Mounting Instruction

Product data

General Information	
Lamp family code	-
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Service tag	Yes
Lighting Technology	LED
Value ladder	Performance

Warranty period	5 years
Sustainability rating	Lighting for circularity
Light Technical	
Luminous Flux	4,000 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	129 lm/W
Color rendering index (CRI)	>80

Datasheet, 2024, November 22 data subject to change

GreenSpace Accent Projector mini


Number of light sources	1
Beam angle of light source	120 degree(s)
Light source color	830 warm white
Optic type	Facetted reflector with beam angle 24
Luminaire light beam spread	24°
Unified glare rating CEN	22
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	- W
Inrush current	11 A
Inrush time	250 ms
Power Consumption	31.5 W
Power Factor (Fraction)	0.9
Connection	3C Track
Cable	-
Number of products on MCB of 16 A type B	30
Suitable for random switching	No
Protection class IEC	Safety class II
Total harmonic distortion	20 %
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Driver/power unit/transformer Control interface	Power supply unit (On/Off)
	Power supply unit (On/Off) - No
Control interface	-
Control interface	-
Control interface Constant light output	-
Control interface Constant light output Mechanical and Housing	- No
Control interface Constant light output Mechanical and Housing Housing Material	- No Aluminum
Control interface Constant light output Mechanical and Housing Housing Material Reflector material	- No Aluminum Polycarbonate aluminum coated
Control interface Constant light output Mechanical and Housing Housing Material Reflector material Optic material	- No Aluminum Polycarbonate aluminum coated Aluminum and polycarbonate
Control interface Constant light output Mechanical and Housing Housing Material Reflector material Optic material Optical cover material	- No Aluminum Polycarbonate aluminum coated Aluminum and polycarbonate
Control interface Constant light output Mechanical and Housing Housing Material Reflector material Optic material Optical cover material Fixation material	- No Aluminum Polycarbonate aluminum coated Aluminum and polycarbonate Polymethyl methacrylate -
Control interface Constant light output Mechanical and Housing Housing Material Reflector material Optic material Optical cover material Fixation material Housing Color	- No Aluminum Polycarbonate aluminum coated Aluminum and polycarbonate Polymethyl methacrylate - Black
Control interface Constant light output Mechanical and Housing Housing Material Reflector material Optic material Optical cover material Fixation material Housing Color Optical cover finish	- No Aluminum Polycarbonate aluminum coated Aluminum and polycarbonate Polymethyl methacrylate - Black Clear
Control interface Constant light output Mechanical and Housing Housing Material Reflector material Optic material Optical cover material Fixation material Housing Color Optical cover finish Overall length	- No Aluminum Polycarbonate aluminum coated Aluminum and polycarbonate Polymethyl methacrylate - Black Clear 181 mm
Control interface Constant light output Mechanical and Housing Housing Material Reflector material Optic material Optical cover material Fixation material Housing Color Optical cover finish Overall length Overall width	- No Aluminum Polycarbonate aluminum coated Aluminum and polycarbonate Polymethyl methacrylate - Black Clear 181 mm 80 mm
Control interface Constant light output Mechanical and Housing Housing Material Reflector material Optic material Optical cover material Fixation material Housing Color Optical cover finish Overall length Overall height	- No Aluminum Polycarbonate aluminum coated Aluminum and polycarbonate Polymethyl methacrylate - Black Clear 181 mm 80 mm 250 mm
Control interface Constant light output Mechanical and Housing Housing Material Reflector material Optic material Optical cover material Fixation material Housing Color Optical cover finish Overall length Overall width Overall diameter	- No Aluminum Polycarbonate aluminum coated Aluminum and polycarbonate Polymethyl methacrylate - Black Clear 181 mm 80 mm 250 mm
Control interface Constant light output Mechanical and Housing Housing Material Reflector material Optic material Optical cover material Fixation material Housing Color Optical cover finish Overall length Overall width Overall height Overall diameter Dimensions (Height x Width x Depth)	- No Aluminum Polycarbonate aluminum coated Aluminum and polycarbonate Polymethyl methacrylate - Black Clear 181 mm 80 mm 250 mm 80 mm
Control interface Constant light output Mechanical and Housing Housing Material Reflector material Optic material Optical cover material Fixation material Housing Color Optical cover finish Overall length Overall width Overall height Overall diameter Dimensions (Height x Width x Depth) Ingress protection code	- No Aluminum Polycarbonate aluminum coated Aluminum and polycarbonate Polymethyl methacrylate - Black Clear 181 mm 80 mm 250 mm 80 mm 190 [Finger-protected]


Approval and Application	
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable
	surfaces
CE mark	Yes
ENEC mark	ENEC mark
Photobiological risk	Photobiological risk group 1 @200mm
	to EN62778
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 ℃
Flickering value (PstLM) - Flickering value as	1
per EN 61000-3-3	
Stroboscopic effect visibility measure (SVM)	0.5
Ambient temperature range	+10 to +35 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.434,0.403)<3
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching	SDCM≤3
(McAdam ellipse)	
Over Time Performance (IEC Compliant)	
Driver failure rate at 5000 h	1%
Control gear failure rate at median useful life	10 %
50000 h	
Lumen maintenance at median useful life*	L90
50000 h	
Lumen maintenance at median useful life*	L85
100000 h	
Product Data	
Order product name	CT21ET ED20C (020 DC) ED24 DV
	ST315T LED39S/830 PSU FR24 BK
Full product name	ST315T LED39S/830 PSU FR24 BK
Full product name Full product code	
	ST315T LED39S/830 PSU FR24 BK
Full product code	ST315T LED39S/830 PSU FR24 BK 871869996521100
Full product code Order code	ST315T LED39S/830 PSU FR24 BK 871869996521100 910505100335
Full product code Order code Material Nr. (12NC)	ST315T LED39S/830 PSU FR24 BK 871869996521100 910505100335 910505100335
Full product code Order code Material Nr. (12NC) Numerator - Quantity Per Pack	ST315T LED39S/830 PSU FR24 BK 871869996521100 910505100335 910505100335
Full product code Order code Material Nr. (12NC) Numerator - Quantity Per Pack EAN/UPC - Product/Case	ST315T LED39S/830 PSU FR24 BK 871869996521100 910505100335 910505100335 1 8718699965211
Full product code Order code Material Nr. (12NC) Numerator - Quantity Per Pack EAN/UPC - Product/Case Numerator - Packs per outer box	ST315T LED39S/830 PSU FR24 BK 871869996521100 910505100335 910505100335 1 8718699965211
Full product code Order code Material Nr. (12NC) Numerator - Quantity Per Pack EAN/UPC - Product/Case Numerator - Packs per outer box EAN/UPC - Case	ST315T LED39S/830 PSU FR24 BK 871869996521100 910505100335 910505100335 1 8718699965211 1 8718699965211

GreenSpace Accent Projector mini

Dimensional drawing









© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.