PHILIPS Lighting



GreenSpace Accent Projector mini

ST315T LED39S/827 PSU FR36 WH

GreenSpace Accent Projector mini, Track projector, 31.5 W, 3900 lm, 2700 K, Facetted reflector with beam angle 36°, White

The GreenSpace Accent Projector mini is the smallest size projector in the GreenSpace Accent range. With a diameter of only 80mm and integrated onboard driver, it offers a clean and small design to be discretely integrated in the store environment. The high performance and Philips Food LED recipes will deliver a strong fit to food retail and small city center store formats. The full range of beam angles and Philips Fashion LED flavors on the other hand, is creating a high quality of light to enhance the fashion collection, making this projector suitable for many different retail applications.

Warnings and Safety

- During manipulation and/or maintenance, the product has to be switched off and cooled down
- The product must be installed out of arm's reach. Manipulating the product when hot is only possible with an insulating glove
- · Luminaire should be installed and removed in accordance to the instructions in the Mounting Instruction

Product data

neral Information		Warranty period	5 years
amp family code	-	Sustainability rating	Lighting for circularity
ght source replaceable	No		
lumber of gear units	1 unit	Light Technical	
ver included	Yes	Luminous Flux	3,900 lm
rvice tag	Yes	Correlated Color Temperature (Nom)	2700 K
ighting Technology	LED	Luminous Efficacy (rated) (Nom)	124 lm/W
alue ladder	Performance	Color rendering index (CRI)	>80


GreenSpace Accent Projector mini

Number of light sources	1	
Number of light sources		
Beam angle of light source	120 degree(s)	
Light source color	827 warm white	
Optic type	Facetted reflector with beam angle 36°	
Luminaire light beam spread	36°	
Unified glare rating CEN	22	
Operating and Electrical		
Input Voltage	220 to 240 V	
Line Frequency	50 to 60 Hz	
Initial CLO power consumption	- W	
Average CLO power consumption	- W	
Inrush current	11 A	
Inrush time	250 ms	
Power Consumption	31.5 W	
Power Factor (Fraction)	0.9	
Connection	3C Track	
Cable	-	
Number of products on MCB of 16 A type B	30	
Suitable for random switching	No	
Protection class IEC	Safety class II	
Total harmonic distortion	20 %	
	20 %	
Controls and Dimming		
Dimmable	No	
Driver/power unit/transformer	Power supply unit (On/Off)	
Control interface	-	
Constant light output	No	
Markenia I and Danis		
Mechanical and Housing		
Housing Material	Aluminum	
Reflector material	Polycarbonate aluminum coated	
Optic material	Aluminum and polycarbonate	
Optical cover material	Polymethyl methacrylate	
Fixation material	-	
Housing Color	White	
Optical cover finish	Clear	
Overall length	181 mm	
Overall width	80 mm	
Overall height	250 mm	
Overall diameter	80 mm	
Dimensions (Height x Width x Depth)	250 x 80 x 181 mm	
Ingress protection code	IP20 [Finger-protected]	
Mech. impact protection code	IK02 [0.2 J standard]	
Optical cover type	Polymethyl methacrylate bowl/cover	
Net Weight (Piece)	0.800 kg	

Approval and Application		
Glow-wire test	Temperature 650 °C, duration 30 s	
Flammability mark	For mounting on normally flammable	
	surfaces	
CE mark	Yes	
ENEC mark	ENEC mark	
Photobiological risk	Photobiological risk group 1@200mm	
	to EN62778	
EU RoHS compliant	Yes	
Performance ambient temperature Tq	25 ℃	
Flickering value (PstLM) - Flickering value as	1	
per EN 61000-3-3		
Stroboscopic effect visibility measure (SVM)	0.5	
Ambient temperature range	+10 to +35 °C	
Initial Performance (IEC Compliant)		
Luminous flux tolerance	+/-10%	
Initial chromaticity	(0.458,0.410)<3	
Power consumption tolerance	+/-10%	
Standard Deviation of Colour Matching	SDCM≤3	
(McAdam ellipse)		
Over Time Performance (IEC Compliant)		
Driver failure rate at 5000 h	1 %	
Control gear failure rate at median useful life	10 %	
50000 h		
Lumen maintenance at median useful life*	L90	
50000 h		
Lumen maintenance at median useful life*	L85	
100000 h		
P. 1. (P. (
Product Data		
Order product name	ST315T LED39S/827 PSU FR36 WH	
	ST315T LED39S/827 PSU FR36 WH ST315T LED39S/827 PSU FR36 WH	
Order product name		
Order product name Full product name	ST315T LED39S/827 PSU FR36 WH	
Order product name Full product name Full product code Order code	ST315T LED39S/827 PSU FR36 WH 871869996517400	
Order product name Full product name Full product code Order code Material Nr. (12NC)	ST315T LED39S/827 PSU FR36 WH 871869996517400 910505100331	
Order product name Full product name Full product code Order code Material Nr. (12NC) Numerator - Quantity Per Pack	ST315T LED39S/827 PSU FR36 WH 871869996517400 910505100331 910505100331 1	
Order product name Full product name Full product code Order code Material Nr. (12NC) Numerator - Quantity Per Pack EAN/UPC - Product/Case	ST315T LED39S/827 PSU FR36 WH 871869996517400 910505100331 910505100331 1 8718699965174	
Order product name Full product name Full product code Order code Material Nr. (12NC) Numerator - Quantity Per Pack EAN/UPC - Product/Case Numerator - Packs per outer box	ST315T LED39S/827 PSU FR36 WH 871869996517400 910505100331 910505100331 1 8718699965174 1	
Order product name Full product name Full product code Order code Material Nr. (12NC) Numerator - Quantity Per Pack EAN/UPC - Product/Case	ST315T LED39S/827 PSU FR36 WH 871869996517400 910505100331 910505100331 1 8718699965174	

GreenSpace Accent Projector mini

Dimensional drawing





© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2024, November 22 - data subject to change