



GreenSpace Accent Projector mini

ST315T LED39S/827 PSU FR36 BK

GreenSpace Accent Projector mini, Track projector, 31.5 W, 3900 lm, 2700 K, Facetted reflector with beam angle 36°, Black

The GreenSpace Accent Projector mini is the smallest size projector in the GreenSpace Accent range. With a diameter of only 80mm and integrated onboard driver, it offers a clean and small design to be discretely integrated in the store environment. The high performance and Philips Food LED recipes will deliver a strong fit to food retail and small city center store formats. The full range of beam angles and Philips Fashion LED flavors on the other hand, is creating a high quality of light to enhance the fashion collection, making this projector suitable for many different retail applications.

Warnings and Safety

- \cdot During manipulation and/or maintenance, the product has to be switched off and cooled down
- · The product must be installed out of arm's reach. Manipulating the product when hot is only possible with an insulating glove
- · Luminaire should be installed and removed in accordance to the instructions in the Mounting Instruction

Product data

General Information	
Lamp family code	-
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Service tag	Yes
Lighting Technology	LED
Value ladder	Performance

Warranty period	5 years
Sustainability rating	Lighting for circularity
Light Technical	
Luminous Flux	3,900 lm
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	124 lm/W
Color rendering index (CRI)	>80

Datasheet, 2024, November 22 data subject to change

GreenSpace Accent Projector mini


Number of light sources	1
Beam angle of light source	120 degree(s)
Light source color	827 warm white
Optic type	Facetted reflector with beam angle 36°
Luminaire light beam spread	36°
Unified glare rating CEN	22
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	- W
Inrush current	11 A
Inrush time	250 ms
Power Consumption	31.5 W
Power Factor (Fraction)	0.9
Connection	3C Track
Cable	-
Number of products on MCB of 16 A type B	30
Suitable for random switching	No
Protection class IEC	Safety class II
Total harmonic distortion	20 %
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum
Reflector material	Polycarbonate aluminum coated
Optic material	Aluminum and polycarbonate
Optical cover material	Polymethyl methacrylate
Fixation material	_
Housing Color	Black
Housing Color Optical cover finish	Black Clear
Optical cover finish	Clear
Optical cover finish Overall length	Clear 181 mm
Optical cover finish Overall length Overall width	Clear 181 mm 80 mm
Optical cover finish Overall length Overall width Overall height	Clear 181 mm 80 mm 250 mm
Optical cover finish Overall length Overall width Overall height Overall diameter	Clear 181 mm 80 mm 250 mm 80 mm
Optical cover finish Overall length Overall width Overall height Overall diameter Dimensions (Height x Width x Depth)	Clear 181 mm 80 mm 250 mm 80 mm 250 x 80 x 181 mm
Optical cover finish Overall length Overall width Overall height Overall diameter Dimensions (Height x Width x Depth) Ingress protection code	Clear 181 mm 80 mm 250 mm 80 mm 250 x 80 x 181 mm IP20 [Finger-protected]


Approval and Application	
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable
	surfaces
CE mark	Yes
ENEC mark	ENEC mark
Photobiological risk	Photobiological risk group 1@200mm to
	EN62778
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Flickering value (PstLM) - Flickering value as	1
per EN 61000-3-3	
Stroboscopic effect visibility measure (SVM)	0.5
Ambient temperature range	+10 to +35 ℃
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.458,0.410)<3
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching	SDCM≤3
(McAdam ellipse)	
Over Time Performance (IEC Compliant)
Driver failure rate at 5000 h	1 %
Control gear failure rate at median useful life	10 %
50000 h	
Lumen maintenance at median useful life*	L90
50000 h	
Lumen maintenance at median useful life*	L85
100000 h	
Product Data	
Order product name	ST315T LED39S/827 PSU FR36 BK
Full product name	ST315T LED39S/827 PSU FR36 BK
Full product code	871869996525900
Order code	910505100339
Material Nr. (12NC)	910505100339
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718699965259
Numerator - Packs per outer box	1
EAN/UPC - Case	8718699965259
Product family code	ST315T [GREENSPACE ACCENT
	PROJECTOR MINI]

GreenSpace Accent Projector mini

Dimensional drawing









© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.