



GreenSpace Accent Gridlight Gen2

GD352B 27S/PC930 DIA-E WB BK

GreenSpace Accent Gridlight Gen2, 2 spots (*flux-performance values for 1 spot), 46 W, C/O 154x304 mm, 2700 lm, PremiumColor, 3000 K, CRI>90, DALI, Interact Ready, Wide beam, PerfectAccent reflector, Black, IP20

With GreenSpace Accent Gridlight Gen2, retailers and building operators can enjoy the superior quality of light and market-leading energy efficiency of PerfectAccent optics in an affordable and sustainable gridlight. Maintenance and upgrades of the driver, LED and optics is easy and requires only standard tools. Because of this, GreenSpace Accent Gridlight Gen2 can support a circular lighting installation. GreenSpace Accent Gridlight Gen2 can be configured as a single-, double- or triple-spothead configurations, in which each spothead can be aimed independently. In addition to dimming options, multiple system integration options are available, including wired and wireless. Check out our Fashion catalog pages to find out more about our PremiumWhite and PremiumColor LED light recipes.

Warnings and Safety

- All photometrical data is calculated without optional front glass. Flux should be reduced by 3.5% when using front glass.
- Cleaning of the optic should be done only with pressurized air. Touching the LED or reflector is forbidden. For food preparation areas and areas with high levels of dust, we strongly advise the use of the optional front glass, as it can be cleaned with a dry microfiber cloth.
- During maintenance, the product must be switched off and cooled down.
- The product must be installed out of arm's reach. Manipulating the product when hot is possible only with an insulated glove.

Product data

GreenSpace Accent Gridlight Gen2

General Information	
Number of gear units	2 units
Driver included	Yes
Service tag	Yes
Value ladder	Performance
Warranty period	5 years
Sustainability rating	Lighting for circularity

Light Technical	
Luminous Flux	2,700 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	117 lm/W
Color rendering index (CRI)	>90
Beam angle of light source	120 degree(s)
Light source color	Premium color with CRI ≥90 and color temperature 3000 K
Optic type	Wide beam
Luminaire light beam spread	36°

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	18 A
Inrush time	250 ms
Power Consumption	46 W
Power Factor (Fraction)	0.9
Connection	2 Push-in connector 2-pole
Cable	-
Number of products on MCB of 16 A type B	34
Suitable for random switching	No
Protection class IEC	Safety class II
Total harmonic distortion	9.5 %

Controls and Dimming	
Dimmable	Yes
Driver/power unit/transformer	Dali dimming Interact System ready external
Control interface	DALI
Constant light output	No
DALI Standard	D4i™ DALI-2™
Maximum dim level	1%
Connectivity	Interact Ready

Mechanical and Housing	
Housing Material	Aluminium
Reflector material	Polycarbonate aluminum coated
Optic material	Aluminum and polycarbonate
Optical cover material	-
Fixation material	-
Housing Color	Black
Optical cover finish	-
Reflector Finish	PerfectAccent reflector

Overall length	324 mm
Overall width	174 mm
Overall height	93 mm
Overall diameter	0 mm
Dimensions (Height x Width x Depth)	93 x 174 x 324 mm
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Explosion hazard class	-
Net Weight (Piece)	1.000 kg

Emergency Operation	
Central Emergency	No

Approval and Application	
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	-
CE mark	Yes
ENEC mark	ENEC mark
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	0.9
Ambient temperature range	+10 to +35 °C

Initial Performance (IEC Compliant)	
Luminous flux tolerance	-10% / +10%
Initial chromaticity	(0.422, 0.386) SDCM <2
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤2

Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 50000 h	10 %
Control gear failure rate at median useful life 100000 h	3.1 %
Lumen maintenance at median useful life* 50000 h	L85
Lumen maintenance at median useful life* 100000 h	L80

Product Data	
Order product name	GD352B 27S/PC930 DIA-E WB BK
Full product name	GD352B 27S/PC930 DIA-E WB BK
Full product code	872016958835600
Order code	910505102777
Material Nr. (12NC)	910505102777
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169588356
Numerator - Packs per outer box	1

GreenSpace Accent Gridlight Gen2

EAN/UPC - Case	8720169588356
Product family code	GD352B [GreenSpace Accent Gridlight G2
	2]

Dimensional drawing

