



# GreenSpace Accent Elbow Gen2

**RS352B 27S/PC930 WIA-E WB ACC WH**

GreenSpace Accent Elbow Gen2, 24 W, C/O D150 mm, 2700 lm, PremiumColor, 3000 K, CRI>90, Wireless, Interact Ready, Wide beam, PerfectAccent reflector, White, IP20

With GreenSpace Accent Elbow Gen2, retailers and building operators can enjoy the superior quality of light and market-leading energy efficiency of PerfectAccent optics in an affordable and sustainable accent downlighter. Maintenance and upgrades of the driver, LED and optics is easy and requires only standard tools. Because of this, GreenSpace Accent Elbow Gen2 can support a circular lighting installation. The luminaire's extractable and rotatable spotlight ensures that light can be aimed where required. In addition to dimming options, multiple system integration options are available, including wired and wireless. Fresh food LED lighting recipes are available for prolonged shelf life, better visual representation of food, reduction of food waste and increased sales. Check out our Fashion and Food catalog pages to find out more about PremiumWhite, PremiumColor, Fresh Meat, Rosé, Frost and Champagne recipes.

## Warnings and Safety

- All photometrical data is calculated without optional front glass. Flux should be reduced by 3.5% when using front glass.
- Cleaning of the optic should be done only with pressurized air. Touching the LED or reflector is forbidden. For food preparation areas and areas with high levels of dust, we strongly advise the use of the optional front glass, as it can be cleaned with a dry microfiber cloth.
- During maintenance, the product must be switched off and cooled down.
- The product must be installed out of arm's reach. Manipulating the product when hot is possible only with an insulated glove.

## Product data

GreenSpace Accent Elbow Gen2

General Information	
Number of gear units	2 units
Driver included	Yes
Service tag	Yes
Value ladder	Performance
Warranty period	5 years
Sustainability rating	Lighting for circularity

Light Technical	
Luminous Flux	2,700 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	113 lm/W
Color rendering index (CRI)	>90
Beam angle of light source	120 degree(s)
Light source color	Premium color with CRI ≥90 and color temperature 3000 K
Optic type	Wide beam
Luminaire light beam spread	36°

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	4.8 A
Inrush time	56 ms
Power Consumption	24 W
Power Factor (Fraction)	0.9
Connection	2 Push-in connector 2-pole
Cable	-
Number of products on MCB of 16 A type B	50
Suitable for random switching	No
Protection class IEC	Safety class II
Total harmonic distortion	10 %

Controls and Dimming	
Dimmable	Yes
Driver/power unit/transformer	Wireless driver Interact System ready external
Control interface	Wireless
Constant light output	No
Maximum dim level	10%
Connectivity	Interact Ready

Mechanical and Housing	
Housing Material	Aluminium
Reflector material	Polycarbonate aluminum coated
Optic material	Aluminum and polycarbonate
Optical cover material	Polymethyl methacrylate
Fixation material	-
Housing Color	White
Optical cover finish	Clear
Reflector Finish	PerfectAccent reflector
Overall length	0 mm

Overall width	0 mm
Overall height	112 mm
Overall diameter	163 mm
Dimensions (Height x Width x Depth)	112 x 0 x 0 mm
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Explosion hazard class	-
Net Weight (Piece)	0.800 kg

Emergency Operation	
Central Emergency	No

Approval and Application	
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	-
CE mark	Yes
ENEC mark	ENEC mark
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	0.9
Ambient temperature range	+10 to +35 °C

Initial Performance (IEC Compliant)	
Luminous flux tolerance	-10% / +10%
Initial chromaticity	(0.422, 0.386) SDCM <2
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤2

Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life	10 %
50000 h	
Lumen maintenance at median useful life*	L85
50000 h	

Product Data	
Order product name	RS352B 27S/PC930 WIA-E WB ACC WH
Full product name	RS352B 27S/PC930 WIA-E WB ACC WH
Full product code	872016958823300
Order code	910505102765
Material Nr. (12NC)	910505102765
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169588233
Numerator - Packs per outer box	1
EAN/UPC - Case	8720169588233
Product family code	RS352B [GreenSpace Accent Elbow G2]

# GreenSpace Accent Elbow Gen2

## Dimensional drawing

