



# CoreLine Panel gen6

RC132V G6 29\_36\_43S/830\_40 PSU W60L60 OC

CoreLine Panel gen6, All-in, 31 W, 22 W, 600x600 mm, VPC, 2900 lm, 3100 lm, 3350 lm, 3600 lm, 4000 lm, 4300 lm, 3000 K, 3500 K, 4000 K

Philips CoreLine panel Gen6 delivers on the CoreLine promise of innovation, easy installation, and excellent illumination. Designed as a direct replacement for functional luminaires in general lighting applications, this LED panel light’s innovative All-in feature offers a choice of three lumen packages and three-color temperatures in a single luminaire. This makes it easy to select the right product, gives you the flexibility respond to customer preferences on site, and means fewer product codes on stock. Installing the CoreLine RC132V LED panel is quick and easy, using the product’s quick connector or flywire. The CoreLine range includes Interact Ready luminaires with integrated wireless communications, ready to be used with Interact gateways, sensors, and software.

## Product data

| General Information                |  |                             |   |
|------------------------------------|--|-----------------------------|---|
| Number of gear units               | 1 unit                                 | Color rendering index (CRI) | >80   |
| Driver included                    | Yes                                    | Beam angle of light source  | 90 degree(s)  |
| Service tag                        | Yes                                    | Light source color          | 840 neutral white                                   |
| Value ladder                       | Performance                            | Optic type                  | Beam angle 90°                                      |
| Warranty period                    | 5 years                                | Luminaire light beam spread | 90°   |
| Sustainability rating              | -                                      | Unified glare rating CEN    | 19  |
|                                    |  | All-in Type                 | All-in, Multi Lumen All-in, Multi Color Temperature |
| Light Technical                    |  | Operating and Electrical    |   |
| Luminous Flux                      | 2,900 3,100 3,350 3,600 4,000 4,300 lm | Input Voltage               | 220 to 240 V  |
| Correlated Color Temperature (Nom) | 3000 3500 4000 K                       | Line Frequency              | 50 or 60 Hz   |
| Luminous Efficacy (rated) (Nom)    | 141 129 lm/W                           |                             |   |

## CoreLine Panel gen6

|  |                          |
|--|--------------------------|
| Inrush current                           | 20 A                     |
| Inrush time                              | 0.22 ms                  |
| Power Consumption                        | 31 22 W                  |
| Power Factor (Fraction)                  | 0.9                      |
| Connection                               | Push-in connector 2-pole |
| Cable                                    | -                        |
| Number of products on MCB of 16 A type B | 21                       |
| Suitable for random switching            | Not applicable           |
| Protection class IEC                     | Safety class II          |
| Total harmonic distortion                | 20 %                     |

### Controls and Dimming

|                               |                                     |
|-------------------------------|-------------------------------------|
| Dimmable                      | No                                  |
| Driver/power unit/transformer | Power supply unit external (On/Off) |
| Control interface             | -                                   |
| Constant light output         | No                                  |
| Maximum dim level             | Not applicable                      |

### Mechanical and Housing

|   |  |
|---|--|
| Housing Material  | Steel  |
| Reflector material  | Acrylate   |
| Optic material  | Polystyrene  |
| Optical cover material                                    | Polystyrene  |
| Fixation material   | -  |
| Housing Color   | White  |
| Optical cover finish                                      | Diamond  |
| Overall length  | 595 mm   |
| Overall width   | 595 mm   |
| Overall height  | 63 mm  |
| Dimensions (Height x Width x Depth)                       | 63 x 595 x 595 mm  |
| Compatible ceiling or ceiling installation accessory type | Visible profile ceiling version                          |
| Ingress protection code                                   | IP20/44 [Finger-protected; wire-protected, splash-proof] |
| Mech. impact protection code                              | IK02 [0.2 J standard]                                    |
| Safety device   | SC [Safety cable]  |
| Net Weight (Piece)  | 2.230 kg   |

### Emergency Operation

|                   |    |
|-------------------|----|
| Central Emergency | No |
|-------------------|----|

### Approval and Application

|                |                                   |
|----------------|-----------------------------------|
| Glow-wire test | Temperature 650 °C, duration 30 s |
|----------------|-----------------------------------|

|   |  |
|---|--|
| Flammability mark   | For mounting on normally flammable surfaces    |
| CE mark   | Yes  |
| ENEC mark   | ENEC mark                                      |
| Photobiological risk  | Photobiological risk group 0 @200mm to EN62778 |
| Photobiological risk specification                              | 0.2 m  |
| EU RoHS compliant   | Yes  |
| Performance ambient temperature Tq                              | 25 °C  |
| Flickering value (PstLM) - Flickering value as per EN 61000-3-3 | 1  |
| Stroboscopic effect visibility measure (SVM)                    | 0.4  |
| Ambient temperature range                                       | -10 to +35 °C                                  |

### Initial Performance (IEC Compliant)

|                             |                      |
|-----------------------------|----------------------|
| Luminous flux tolerance     | -10% / +10%          |
| Initial chromaticity        | (0.38, 0.38) SDCM ≤3 |
| Power consumption tolerance | +/-10%               |

### Over Time Performance (IEC Compliant)

|   |         |
|---|---------|
| Control gear failure rate at median useful life 50000 h | 5 %     |
| Lumen maintenance at median useful life* 50000 h        | L90 L85 |
| Lumen maintenance at median useful life* 100000 h       | L75 L80 |

### Product Data

|                                 |  |
|---------------------------------|--|
| Order product name              | RC132V G6 29_36_43S/830_40 PSU W60L60 OC |
| Full product name               | RC132V G6 29_36_43S/830_40 PSU W60L60 OC |
| Full product code               | 872016973518799                          |
| Order code                      | 911401891185                             |
| Material Nr. (12NC)             | 911401891185                             |
| Numerator - Quantity Per Pack   | 1  |
| EAN/UPC - Product/Case          | 8720169735187                            |
| Numerator - Packs per outer box | 4  |
| EAN/UPC - Case                  | 8720169735330                            |

## CoreLine Panel gen6

### Dimensional drawing

