



Coreline tempo large

BVP130 LED260-4S/840 PSU OFA52 ALU C1KC3

Coreline tempo large, Floodlight, 205 W, 25000 lm, 4000 K, CRI80, Asymmetrical, IP66

CoreLine tempo large delivers on the CoreLine promise of innovative, easy to use and high quality luminaires. A narrow range of options makes it easy to find the best lux-for-lux replacement for 150W, 250W, and 400W HID lamps. The CoreLine tempo large floodlighting range offers lumen packages for many different application areas as well as a choice of high-performance asymmetrical and symmetrical optics. The installation is made easy thanks to the U-shaped universal mounting bracket and the external quick 3-poles connector. It is an ideal solution for outdoor areas such as tempo floodlights for industrial/commercial areas, parking lots, etc.

Product data

| General Information | |
|---------------------------|---|
| Lamp family code | LED260-4S [LED module, system flux 26000 lm] |
| Number of gear units | 1 unit |
| Driver included | Yes |
| Light source engine type | LED |
| Service tag | Yes |
| Value ladder | Performance |
| Serviceability class | Class C, luminaire without serviceable parts, not serviceable |
| Warranty period | 5 years |
| Sustainability rating | - |
| Light Technical | |
| Upward light output ratio | 0 |

| Luminous Flux | 25,000 lm |
|------------------------------------|-------------------|
| Correlated Color Temperature (Nom) | 4000 K |
| Luminous Efficacy (rated) (Nom) | 124 lm/W |
| Color rendering index (CRI) | 80 |
| Light source color | 840 neutral white |
| Luminaire light beam spread | 52° x 102° |
| Optic type outdoor | Asymmetrical |
| Effective projected area | 0.15 m² |
| Operating and Electrical | |
| Input Voltage | 220 to 240 V |
| Line Frequency | 50 to 60 Hz |
| Inrush current | 53 A |
| Inrush time | 0.3 ms |
| Power Consumption | 205 W |

Coreline tempo large

| | |
|--|--|
| Power Factor (Fraction) | 0.97 |
| Connection | External connector |
| Cable | Cable 1.0 m with plug Wieland/Adels compatible 3-pole |
| Number of products on MCB of 16 A type B | 8 |
| Protection class IEC | Safety class I |
| Surge Protection (Common/Differential) | Luminaire surge protection level until 6 kV differential mode and 8 kV common mode |

Controls and Dimming

| | |
|-------------------------------|----------------------------|
| Dimmable | No |
| Driver/power unit/transformer | Power supply unit (On/Off) |
| Constant light output | No |

Mechanical and Housing

| | |
|-------------------------------------|--|
| Housing Material | Aluminum |
| Reflector material | - |
| Optic material | Polycarbonate |
| Optical cover material | Glass |
| Fixation material | Aluminum |
| Housing Color | Grey |
| Mounting device | Wall-mounting bracket |
| Optical cover shape | Flat |
| Optical cover finish | Clear |
| Overall length | 340.5 mm |
| Overall width | 422 mm |
| Overall height | 40 mm |
| Dimensions (Height x Width x Depth) | 40 x 422 x 341 mm |
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK08 [5 J vandal-protected] |
| Standard tilt angle posttop | 0° |
| Standard tilt angle side entry | 0° |
| Optical cover type | Flat glass |
| Net Weight (Piece) | 7.800 kg |

Emergency Operation

| | |
|--------------------|----|
| Central Emergency | No |
| Emergency lighting | - |

Approval and Application

| | |
|------------------------------------|--|
| Flammability mark | For mounting on normally flammable surfaces |
| CE mark | Yes |
| ENEC mark | ENEC mark |
| Photobiological risk | Photobiological risk group 1 @200mm to EN62778 |
| EU RoHS compliant | Yes |
| Performance ambient temperature Tq | 25 °C |
| Ambient temperature range | -40 to +45 °C |

Initial Performance (IEC Compliant)

| | |
|---------------------------------------|------------------------|
| Luminous flux tolerance | +/-7% |
| Initial chromaticity | (0.434, 0.403) SDCM <5 |
| Power consumption tolerance | +/-10% |
| Init. Color Rendering Index Tolerance | +/-2 |

Over Time Performance (IEC Compliant)

| | |
|--|------|
| Control gear failure rate at median useful life 100000 h | 10 % |
| Lumen maintenance at median useful life* 100000 h | L80 |

Product Data

| | |
|---------------------------------|--|
| Order product name | BVP130 LED260-4S/840 PSU OFA52 ALU C1KC3 |
| Full product name | BVP130 LED260-4S/840 PSU OFA52 ALU C1KC3 |
| Full product code | 872016979981300 |
| Order code | 912300060604 |
| Material Nr. (12NC) | 912300060604 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8720169799813 |
| Numerator - Packs per outer box | 1 |
| EAN/UPC - Case | 8720169799813 |
| Product family code | BVP130 [CORELINE TEMPO LARGE] |

Coreline tempo large

Dimensional drawing

