



DigiStreet

BGP760 LED60/740 I DX10 DGR CLO IACZ-4-D

DigiStreet, Road & street light, 37 W, 4988 lm, 4000 K, CRI70, GPRS network, Distribution extra wide 10, Safety class I, IP66

Developed with the aim to become your long term partner „ the system ready architecture of DigiStreet enables you to enjoy the benefits of connected lighting systems today and also gets the city ready for the innovations to come!. Its two sockets enable you to connect directly to the Philips CityTouch system and is also prepared to connect you to the future innovations of IoT. Next to this, each individual luminaire is uniquely identifiable, thanks to the Philips Service tag application. With a simple scan of a QR code, placed on the inside of the mast door, you gain instant access to the luminaire configuration, making maintenance and programming operations faster and easier, no matter what stage of the luminaire’s lifetime. Digistreet is also equipped with dedicated light recipes that: 1) maintain an optimal ecosystems for bats or 2) preserve a dark night sky.

Product data

General Information		protection device, optics, front cover and mechanical parts	
Lamp family code	LED60 [LED module 6000 lm]	Warranty period	5 years
Light source replaceable	Yes	Sustainability rating	Lighting for circularity
Number of gear units	1 unit		
Driver included	Yes	Light Technical	
Light source engine type	LED	Upward light output ratio	0
Service tag	Yes	Luminous Flux	4,988 lm
Lighting Technology	LED	Correlated Color Temperature (Nom)	4000 K
Value ladder	Specification	Luminous Efficacy (rated) (Nom)	141 lm/W
Serviceability class	Class A, luminaire is equipped with serviceable parts (when applicable): LED board, driver, control units, surge	Color rendering index (CRI)	70
		Light source color	740 neutral white

Luminaire light beam spread	151° - 43° x 67°
Optic type outdoor	Distribution extra wide 10
Effective projected area	0.0578 m²

Operating and Electrical

Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Initial CLO power consumption	36.5 W
Average CLO power consumption	37 W
End CLO power consumption	37.5 W
Inrush current	21 A
Inrush time	0.3 ms
Power Consumption	37 W
Power Factor (Fraction)	0.98
Connection	Screw connector
Cable	-
Number of products on MCB of 16 A type B	21
Protection class IEC	Safety class I
Surge Protection (Common/Differential)	Luminaire surge protection level until 6 kV differential mode and 8 kV common mode

Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI and SystemReady interface
Control interface	GPRS network
Constant light output	Yes
Maximum dim level	0% (digital)

Mechanical and Housing

Housing Material	Aluminum die cast
Reflector material	Polycarbonate
Optic material	Acrylate
Optical cover material	Glass
Fixation material	Stainless steel
Housing Color	Dark gray
Mounting device	Spigot for diameter 76 mm
Optical cover shape	Flat
Optical cover finish	Clear
Overall length	752 mm
Overall width	236 mm
Overall height	130 mm
Dimensions (Height x Width x Depth)	130 x 236 x 752 mm
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK09 [10 J]
Standard tilt angle posttop	0°
Standard tilt angle side entry	0°
Optical cover type	Flat glass

Net Weight (Piece)	6.027 kg
--------------------	----------

Approval and Application

Flammability mark	-
CE mark	Yes
ENEC mark	ENEC mark
Photobiological risk	Photobiological risk group 0 @200mm to EN62778
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Remarks	* At extreme ambient temperatures the luminaire might automatically dim down to protect components
Ambient temperature range	-40 to +50 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Initial chromaticity	(0.38, 0.38) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤5

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 50000 h	L100
Lumen maintenance at median useful life* 100000 h	L100

Product Data

Order product name	BGP760 LED60/740 I DX10 DGR CLO IACZ-4-D
Full product name	BGP760 LED60/740 I DX10 DGR CLO IACZ-4-D
Full product code	871951418218900
Order code	910925867978
Material Nr. (12NC)	910925867978
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514182189
Numerator - Packs per outer box	1
EAN/UPC - Case	8719514182189
Product family code	BGP760 [DigiStreet Micro]

Dimensional drawing

