



LumiStreet gen2

BGP292 LED70-4S/740 II DM11 48/76S POLE

LumiStreet gen2, Road & street light, 40.5 W, 6090 lm, 4000 K, CRI70, Distribution medium 11, Safety class II, IP66

Increasing numbers of municipalities are having to upgrade large-scale conventional street lighting installations with energy efficient LED technology. But they are having to do this with smaller and smaller budgets. That's why the new generation of LumiStreet has been upgraded and designed to provide a solution to this challenge, it is the ideal solution for performing point-to-point replacement of conventional lighting. LumiStreet gen2 achieves this by offering high efficiency, low Total Cost of Ownership, and ease of installation and maintenance. The ease of installation and maintenance is enabled by the Philips Service tag. Moreover, the Philips SR (System Ready) socket makes it future-ready and you can pair this luminaire with lighting control and software applications such as Interact City.

Product data

General Information		Warranty period	
Lamp family code	LED70 [LED module 7000 lm]	5 years	
Light source replaceable	Yes	Sustainability rating	
Number of gear units	1 unit	Lighting for circularity	
Driver included	Yes	Light Technical	
Light source engine type	LED	Upward light output ratio	
Service tag	Yes	0	
Lighting Technology	LED	Luminous Flux	
Value ladder	Specification	6,090 lm	
Serviceability class	Class A, luminaire is equipped with serviceable parts (when applicable): LED board, driver, control units, surge protection device, optics, front cover and mechanical parts	Correlated Color Temperature (Nom)	
		4000 K	
		Luminous Efficacy (rated) (Nom)	
		150 lm/W	
		Color rendering index (CRI)	
		70	
		Light source color	
		740 neutral white	
		Luminaire light beam spread	
		160° - 42° x 54°	
		Optic type outdoor	
		Distribution medium 11	

LumiStreet gen2

Effective projected area	0.0251 m²
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	47 A
Inrush time	0.25 ms
Power Consumption	40.5 W
Power Factor (Fraction)	0.98
Connection	2 Push-in connector 5-pole
Cable	-
Number of products on MCB of 16 A type B	10
Protection class IEC	Safety class II
Surge Protection (Common/Differential)	Luminaire surge protection level until 6 kV differential mode and 8 kV common mode
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit regulating
Control interface	-
Constant light output	No
Maximum dim level	0% (digital)
Mechanical and Housing	
Housing Material	Aluminum die cast
Reflector material	Polycarbonate
Optic material	Polymethyl methacrylate
Optical cover material	Glass
Fixation material	Aluminum
Housing Color	Gray
Mounting device	Side-entry for diameter 76 mm
Optical cover shape	Flat
Optical cover finish	Clear
Overall length	620 mm
Overall width	234 mm
Overall height	95 mm
Dimensions (Height x Width x Depth)	95 x 234 x 620 mm
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK09 [10 J]
Standard tilt angle posttop	0°
Standard tilt angle side entry	0°
Optical cover type	Flat glass
Net Weight (Piece)	5.340 kg
Approval and Application	
Flammability mark	For mounting on normally flammable surfaces

CE mark	Yes
ENEC mark	ENEC plus mark
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Remarks	* At extreme ambient temperatures the luminaire might automatically dim down to protect components
Ambient temperature range	-40 to +50 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-7%
Initial chromaticity	(0.381, 0.379) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤5
Over Time Performance (IEC Compliant)	
Driver failure rate at 5000 h	0.5 %
Control gear failure rate at median useful life 50000 h	5 %
Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 50000 h	L99
Lumen maintenance at median useful life* 100000 h	L97
Product Data	
Order product name	BGP292 LED70-4S/740 II DM11 48/76S POLE
Full product name	BGP292 LED70-4S/740 II DM11 48/76S POLE
Full product code	871951412564300
Order code	910925867781
Material Nr. (12NC)	910925867781
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514125643
Numerator - Packs per outer box	1
EAN/UPC - Case	8719514125643
Product family code	BGP292 [LumiStreet gen2 Mini]

Dimensional drawing

