ToLEDo Performer T60 2300LM 840 E27 SL

Item No: 0028369







Direct retrofit replacement for high-pressure mercury vapor lamps (HPMV)50,000 hours average rated lifetimeUp to 78% energy saving compared to the standard high-pressure mercury vapor lampsMercury-free solutionLower maintenance costHigh lumen efficacyDual operating mode – compatible with HPMV magnetic ballast and also, suitable for AC direct mains 120-240V operationHigh surge voltage protection: 4kVSuitable for both open and enclosed luminairesWide light distributionHigh switching cycles – 200,000XHigh colour rendering – CRI80Minimum and maximum operating temperature: -30°C to 50°C

Technical Assets

Dimensions (mm)



Photometrics





ToLEDo Performer T60 2300LM 840 E27 SL

Item No: 0028369

SYLVANIA

General data

| Product name | ToLEDo Performer T60 2300LM 840 E27 SL |
|--|---|
| Technology | LED |
| Watt (Rated) (W) | 18 |
| Cap/Base | E27 |
| Fixture rating | Open |
| General application | Logistics & Industry |
| Operating temperature range (°C) | -20°C+50°C |
| Performance ambient temperature Tq (°C) | 25 |
| ETIM Class | EC001959 |
| E-number Fl | 4844489 |
| Warranty | 5 years |

Optical data

| Useful luminous flux (Фuse) | 2300 |
|--|------------|
| Luminous flux (Rated) (lm) | 2300 |
| Correlated colour temperature (k) | 4000 |
| Light colour | Cool White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM6 |
| Photobiological Risk Group | RG1 |
| Lumen maintenance at end of nominal life (%) | 70 |

Electrical data

| Power consumption (W) | 18 |
|--|---------|
| Wattage (W) | 18 |
| Starting time (max) (s) | 0.5 |
| Warm-up time to 60% of full light (max) (s) | 0.5 |
| Primary Supply/Product voltage - min (V) | 220 |
| Primary Supply/Product voltage - max (V) | 240 |
| Lamp power factor | 1 |
| Control gear required | No |
| No. Of switching cycles before premature failures | >200000 |
| Dimmable | No |
| Inrush Current (A) | 78.8 |
| Inrush Duration (µs) | 2 |
| Lamp Energy Label (class) | E |
| Nominal Frequency (Hz) | 50/60Hz |
| Max. products per 16A C Breaker | 80 |

Lifetime data

| Lifespan L70 B50 | 50000 |
|----------------------------|-------|
| Average life (Nominal) (h) | 50000 |
| Average life (Rated) (h) | 50000 |

Physical data

| Nominal Product Length (mm) | 150 |
|-------------------------------|-------|
| Nominal Product Diameter (mm) | 60 |
| Weight (kg) | 0.312 |

ToLEDo Performer T60 2300LM 840 E27 SL

Item No: 0028369



Packaging

| Product EAN number | 5410288283692 |
|---------------------------------------|----------------|
| Packaging single length / height (cm) | 7.3 |
| Packaging single width (cm) | 7.3 |
| Packaging single depth (cm) | 22.5 |
| DUN14 (inner) | 15410288283699 |
| Units per outer package | 6 |
| Packaging outer length / height (cm) | 23.6 |
| Packaging outer width (cm) | 16.4 |
| Packaging outer depth (cm) | 24.6 |

Safety data

| • | |
|-------------------------------------|---|
| Optimal operating condition (°C) | -20-50 |
| Breakage cleaning instructions | Not applicable |
| Special purpose lamp | No |
| Dry applications use only | No |
| Suitable for household illumination | Yes |
| Safety message | Not Suitable for totally enclosed fixtures |