ToLEDo Performer T85 4500LM 840 E27 SL

Item No: 0028371

















Direct retrofit replacement for high-pressure mercury vapor lamps (HPMV)50,000 hours average rated lifetimeUp to 78% energy saving compared to the standard high-pressure mercury vapor lampsMercury-free solutionLower maintenance costHigh lumen efficacyDual operating mode – compatible with HPMV magnetic ballast and also, suitable for AC direct mains 120-240V operationHigh surge voltage protection: 4kVSuitable for both open and enclosed luminairesWide light distributionHigh switching cycles – 200,000XHigh colour rendering – CRI80Minimum and maximum operating temperature: -30°C to 50°C

Technical Assets

Dimensions (mm)



Photometrics



ToLEDo Performer T85 4500LM 840 E27 SL

Item No: 0028371



Ge	ner	، اھ	d	ata
uc				

Product name	ToLEDo Performer T85 4500LM 840 E27 SL
Technology	LED
Watt (Rated) (W)	36
Cap/Base	E27
Fixture rating	Open
General application	Logistics & Industry
Operating temperature range (°C)	-20°C+50°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740740
Warranty	5 years

Optical data

- p	
Useful luminous flux (Фuse)	4500
Luminous flux (Rated) (lm)	4500
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

Electrical data

36
36
0.5
0.5
220
240
0.95
No
>200000
No
80.8
2
E
50/60Hz
40

Lifetime data

Lifespan L70 B50	50000
Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000

Physical data

Nominal Product Length (mm)	204
Nominal Product Diameter (mm)	85
Weight (kg)	0.646

ToLEDo Performer T85 4500LM 840 E27 SL

Item No: 0028371



Packaging

Product EAN number	5410288283715
Packaging single length / height (cm)	9.5
Packaging single width (cm)	9.5
Packaging single depth (cm)	25.0
DUN14 (inner)	15410288283712
Units per outer package	6
Packaging outer length / height (cm)	30.4
Packaging outer width (cm)	20.9
Packaging outer depth (cm)	27.2

Safety data

Optimal operating condition (°C)	-20-50	
Breakage cleaning instructions	Not applicable	
Special purpose lamp	No	
Dry applications use only	No	
Suitable for household illumination	Yes	
Safety message	Not Suitable for totally enclosed fixtures	