ToLEDo Superia T5 AC V2 4FT 3900LM

Item No: 0029257
















50,000 hours average rated lifetime Last 2.5 times longer than 54W 1149mm fluorescent tri-phosphor T5 lamp High switching cycles - 200,000X Omni-directional light distribution and wide beam angle Minimum and maximum operating temperature: -20°C to 50°C Glass construction and polycarbonate end-caps Only suitable for direct mains (AC 220-240V) operation Ideal for factories, parking lots, supermarkets, department stores, schools and offices Not suitable for operation with electronic/ECG or magnetic/CCG ballasts

Technical Assets

Dimensions (mm)

Photometrics



ToLEDo Superia T5 AC V2 4FT 3900LM

T5 AC

Item No: 0029257

General data



Product name	ToLEDo Superia T5 A V2 4FT 3900LM 840
Technology	LED
Watt (Rated) (W)	26

Lamp shape Tube, double-ended Cap/Base G5

Lamp finish Opal Fixture rating Open

Education, Hospitality, Logistics & Industry, **General application** Museums & Galleries, Office, Residential & Consumer, Retail

EC001959

-20°C...+45°C Operating temperature range (°C) Performance ambient temperature Tq

25 (°C)

4940789 E-number FI

Warranty 5 years

Optical data

ETIM Class

Useful luminous flux (Φuse)	3900
Luminous flux (Rated) (Im)	3900
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	150
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

Electrical data

Power consumption (W)	26
Wattage (W)	26
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
Control gear required	No
No. Of switching cycles before premature failures	>100000
Dimmable	No
Inrush Current (A)	18.0
Inrush Duration (µs)	6
Lamp Energy Label (class)	D
Max. products per 16A C Breaker	67
Max. products per 20A C Breaker	83
Max. products per 10A B Breaker	42
Max. products per 13A B Breaker	55
Max. products per 16A B Breaker	67

Lifetime data

Lifespan L70 B50	50000
Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000

Physical data

IP rating	IP20
Nominal Product Length (mm)	1162
Nominal Product Diameter (mm)	17
Weight (kg)	0.14

ToLEDo Superia T5 AC V2 4FT 3900LM 840

Item No: 0029257



Packaging

Product EAN number	5410288292571
Packaging single length / height (cm)	116.0
Packaging single width (cm)	2.0
Packaging single depth (cm)	2.0
DUN14 (inner)	15410288292578
Units per outer package	10
Packaging outer length / height (cm)	122.0
Packaging outer width (cm)	15.5
Packaging outer depth (cm)	8.0

Safety data

Optimal operating condition (°C)	-20-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture