## ToLEDo Superia T5 AC V2 5FT 3900LM 840

Item No: 0029259






50,000 hours average rated lifetime Last 2.5 times longer than 49W 1449mm fluorescent tri-phosphor T5 lamp High switching cycles - 200,000X Omni-directional light distribution and wide beam angle Minimum and maximum operating temperature: -20°C to 50°C Glass construction and polycarbonate end-caps Only suitable for direct mains (AC 220-240V) operation Ideal for factories, parking lots, supermarkets, department stores, schools and offices Not suitable for operation with electronic/ECG or magnetic/CCG ballasts

## **Technical Assets**

### Dimensions (mm)

**Photometrics** 



## ToLEDo Superia T5 AC V2 5FT 3900LM 840

**Electrical data** 

### Item No: 0029259



### General data

| Product name                               | ToLEDo Superia T5 AC<br>V2 5FT 3900LM 840   | Power consumption (W)                                | 26      |
|--|---|--|---------|
| Technology                                 | LED   | Wattage (W)  | 26      |
| Watt (Rated) (W)                           | 26  | Primary Supply/Product voltage - min<br>(V)          | 220     |
| Lamp shape                                 | Tube, double-ended  | Primary Supply/Product voltage - max                 | 240     |
| Cap/Base                                   | G5  | (M)  | 240     |
| Lamp finish                                | Opal  | Lamp power factor                                    | 0.9     |
| Fixture rating                             | Open  | Control gear required                                | No      |
| General application                        | Education, Hospitality,<br>Logistics & Industry,<br>Museums & Galleries,<br>Office, Residential & | No. Of switching cycles before<br>premature failures | >100000 |
|  |   | Dimmable   | No      |
|  | Consumer, Retail  | Inrush Current (A)                                   | 18.0    |
| Operating temperature range (°C)           | -20°C+45°C  | Inrush Duration (µs)                                 | 6       |
| Performance ambient temperature Tq<br>(°C) | 25  | Lamp Energy Label (class)                            | D       |
| ETIM Class                                 | EC001959  | Max. products per 16A C Breaker                      | 67      |
| E-number Fl                                | 4940791   | Max. products per 20A C Breaker                      | 83      |
| Warranty                                   | 5 years   | Max. products per 10A B Breaker                      | 42      |
| Optical data                               |   | Max. products per 13A B Breaker                      | 55      |
| Useful luminous flux (Физе)                | 3900  | Max. products per 16A B Breaker                      | 67      |
| Luminous flux (Rated) (Im)                 | 3900  | Lifetime data  |         |
| Correlated colour temperature (k)          | 4000  | Lifespan L70 B50                                     | 50000   |
| Light colour                               | Cool White  | Average life (Nominal) (h)                           | 50000   |
| CRI (Ra)                                   | 80  | Average life (Rated) (h)                             | 50000   |
| Colour Variation Initial (SDCM)            | SDCM6   | Physical data  |         |
| Beam Angle (°)                             | 150   | IP rating  | IP20    |
| Photobiological Risk Group                 | RG0   | Nominal Product Length (mm)                          | 1462    |
| Lumen maintenance at end of                |   |  |         |

Nominal Product Diameter (mm)

Weight (kg)

17

0.17

Lumen maintenance at end of nominal life (%)

70

# ToLEDo Superia T5 AC V2 5FT 3900LM 840

### Item No: 0029259



### Packaging

| Product EAN number                    | 5410288292595  |  |
|---------------------------------------|----------------|--|
| Packaging single length / height (cm) | 146.2          |  |
| Packaging single width (cm)           | 1.8            |  |
| Packaging single depth (cm)           | 1.8            |  |
| DUN14 (inner)                         | 15410288292592 |  |
| Units per outer package               | 10             |  |
| Packaging outer length / height (cm)  | 152.1          |  |
| Packaging outer width (cm)            | 15.5           |  |
| Packaging outer depth (cm)            | 7.8            |  |

### Safety data

| ,                                   |                                       |
|-------------------------------------|---------------------------------------|
| Optimal operating condition (°C)    | -20-45                                |
| Breakage cleaning instructions      | Not applicable                        |
| Special purpose lamp                | No                                    |
| Suitable for household illumination | Yes                                   |
| Safety message                      | Suitable for totally enclosed fixture |