

ToLEDo Superia T8 Universal V3 4FT 2400LM 865

Item No: 0029276



50,000 hours average rated life Last 2.5 times longer than 1200mm 36W fluorescent T8 Tri-phosphor lamp High switching cycles – 200,000X High lumen efficacy - 150lm/W Omni-directional light distribution and wide beam angle Minimum and maximum operating temperature: -20°C to 50°C Glass construction and polycarbonate end-caps Works only with compatible electronic ballast Must replace the fluorescent starter with LED dummy starter when used with magnetic/ CCG ballast Suitable for direct mains operation (AC 220-240V) with single-end AC input Ideal for factories, parking lots, supermarkets, department stores, schools and offices

Technical Assets

Photometrics

General data

Product name	ToLEDo Superia T8 Universal V3 4FT 2400LM 865
Technology	LED
Watt (Rated) (W)	16
Lamp shape	Tube, double-ended
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
Operating temperature range (°C)	-20°C...+45°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
Warranty	5 years

Optical data

Useful luminous flux (Φuse)	2400
Luminous flux (Rated) (lm)	2400
Correlated colour temperature (k)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	160
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

ToLEDo Superia T8 Universal V3 4FT 2400LM 865

Item No: 0029276



Electrical data

Power consumption (W)	16
Wattage (W)	16
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
Control gear required	No
No. Of switching cycles before premature failures	>100000
Dimmable	No
Inrush Current (A)	5.3
Inrush Duration (µs)	49
Lamp Energy Label (class)	D
Max. products per 16A C Breaker	52
Max. products per 16A B Breaker	85

Lifetime data

Lifespan L70 B50	50000
Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000

Physical data

IP rating	IP20
Nominal Product Length (mm)	1213
Nominal Product Diameter (mm)	28
Weight (kg)	0.18

Packaging

Product EAN number	5410288292762
Packaging single length / height (cm)	121.0
Packaging single width (cm)	3.0
Packaging single depth (cm)	3.0
DUN14 (inner)	15410288292769
Units per outer package	10
Packaging outer length / height (cm)	120.7
Packaging outer width (cm)	21.0
Packaging outer depth (cm)	11.5

Safety data

Optimal operating condition (°C)	-20-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	None