

ToLEDo GLS 806LM 827 E27 SL10


Item No: 0029650



Compact and elegant designSuitable replacement for halogen, incandescent and compact fluorescent lampsInstant light at the flick of a switchUniform light distributionGood colour rendering (CRI 80)Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areasLower maintenance costs12,000 hours average rated life

Technical Assets

Dimensions (mm)



Photometrics

ToLEDo GLS 806LM 827 E27 SL10

Item No: 0029650



General data

Product name	ToLEDo GLS 806LM 827 E27 SL10
Technology	LED
Watt (Rated) (W)	8
Cap/Base	E27
Fixture rating	Open
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4741167
Warranty	3 years

Optical data

Useful luminous flux (Φuse)	806
Luminous flux (Rated) (lm)	806
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

Electrical data

Power consumption (W)	8
Wattage (W)	8
Equivalent watt (W)	60
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Control gear required	No
No. Of switching cycles before premature failures	>100000
Dimmable	No
Inrush Current (A)	3.2
Inrush Duration (µs)	350
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	50
Max. products per 16A B Breaker	25

Lifetime data

Lifespan L70 B50	12000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	107
Nominal Product Diameter (mm)	60
Weight (kg)	0.295

ToLEDo GLS 806LM 827 E27 SL10

Item No: 0029650



Packaging

Product EAN number	5410288296500
Packaging single length / height (cm)	26.6
Packaging single width (cm)	12.0
Packaging single depth (cm)	11.4
DUN14 (inner)	15410288296507
Units per outer package	6
Packaging outer length / height (cm)	37.9
Packaging outer width (cm)	27.6
Packaging outer depth (cm)	24.1

Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not Applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures