ToLEDo SUPERIA T5 AC V2 5FT 5600LM 840

Item No: 0029260
















50,000 hours average rated lifetime Last 2.5 times longer than 80W 1449mm fluorescent tri-phosphor T5 lamp High switching cycles - 200,000X Omni-directional light distribution and wide beam angle Minimum and maximum operating temperature: -20°C to 50°C Glass construction and polycarbonate end-caps Only suitable for direct mains (AC 220-240V) operation Ideal for factories, parking lots, supermarkets, department stores, schools and offices Not suitable for operation with electronic/ECG or magnetic/CCG ballasts

Technical Assets

Dimensions (mm)

Photometrics



ToLEDo SUPERIA T5 AC V2 5FT 5600LM 840

Item No: 0029260



| G | ρı | ne | ra | I d | lata |
|---|----|----|----|-----|------|
| | | | | | |

| Product name | Toledo Superia T5 AC V2 5FT 5600LM 840 |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------|
| Technology | LED |
| Watt (Rated) (W) | 37 |
| Lamp shape | Tube, double-ended |
| Cap/Base | G5 |
| Lamp finish | Opal |
| Fixture rating | Open |
| General application | Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer |
| Operating temperature range (°C) | -20°C+45°C |
| Performance ambient temperature Tq (°C) | 25 |
| ETIM Class | EC001959 |
| E-number Fl | 4941334 |
| Warranty | 5 years |

Optical data

| - p | |
|----------------------------------------------|------------|
| Useful luminous flux (Φuse) | 5600 |
| Luminous flux (Rated) (Im) | 5600 |
| Correlated colour temperature (k) | 4000 |
| Light colour | Cool White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM6 |
| Beam Angle (°) | 150 |
| Photobiological Risk Group | RG0 |
| Lumen maintenance at end of nominal life (%) | 70 |

Electrical data

| Power consumption (W) | 37 |
|--------------------------------------------------|------------------|
| Wattage (W) | 37 |
| Primary Supply/Product voltage - min (V) | 220 |
| Primary Supply/Product voltage - max (V) | 240 |
| Lamp power factor | 0.9 |
| Control gear required | No |
| No. Of switching cycles before | |
| premature failures | >100000 |
| | >100000 No |
| premature failures | |
| premature failures Dimmable | No |
| premature failures Dimmable Inrush Current (A) | No 24.4 |
| Dimmable Inrush Current (A) Inrush Duration (µs) | No 24.4 13 |

Lifetime data

| Lifespan L70 B50 | 50000 |
|----------------------------|-------|
| Average life (Nominal) (h) | 50000 |
| Average life (Rated) (h) | 50000 |

Physical data

| ir raung | IP20 |
|-------------------------------|------|
| Nominal Product Length (mm) | 1462 |
| Nominal Product Diameter (mm) | 17 |
| Weight (kg) | 0.17 |

Toledo Superia T5 ac V2 5FT 5600LM 840

Item No: 0029260



Packaging

| Product EAN number | 5410288292601 |
|---------------------------------------|----------------|
| Packaging single length / height (cm) | 146.2 |
| Packaging single width (cm) | 1.8 |
| Packaging single depth (cm) | 1.8 |
| DUN14 (inner) | 15410288292608 |
| Units per outer package | 10 |
| Packaging outer length / height (cm) | 152.1 |
| Packaging outer width (cm) | 15.5 |
| Packaging outer depth (cm) | 7.8 |

Safety data

| Optimal operating condition (°C) | -20-45 |
|-------------------------------------|---------------------------------------|
| Breakage cleaning instructions | Not applicable |
| Special purpose lamp | No |
| Suitable for household illumination | Yes |
| Safety message | Suitable for totally enclosed fixture |