RefLED Platinum Retro ES50 350LM **DIM 830 36 SL**

Item No: 0030370




















Ultra-efficient LED GU10 range with the same look and size as traditional GU10 lampSave up to 95% on energy bills compared to halogen GU10 lampsEnergy Class B and best-in-class lumen efficacySustainable and eco-friendly solutionRecreates backlight effect like halogen dichroic GU10 lampsFull glass design - means no colours clashing between lamps and fixtureLast three times longer than the standard LED retrofit lampsRemarkable 50,000 hours average rated life – reducing the hassle of frequent replacementsCOOLFIT functionality – ensures overheating and overtemperature protectionIdeal for everyday lighting in homes, hotels, restaurants and moreDimmable

Technical Assets

Dimensions (mm)



Photometrics

RefLED Platinum Retro ES50 350LM DIM 830 36 SL

Item No: 0030370



General data

Product name	RefLED Platinum Retro ES50 350LM DIM 830 36 SL
Technology	LED
Lamp shape	Reflector
Cap/Base	GU10
Lamp finish	None
Fixture rating	Open
General application	Education, Hospitality, Museums & Galleries, Office, Residential & Consumer, Retail
Operating temperature range (°C)	-20°C+50°C
ETIM Class	EC001959
E-number FI	4741182
Warranty	5 years

Optical data

Useful luminous flux (⊕use)	350
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Luminous Intensity (cd)	850
Beam Angle (°)	36
Photobiological Risk Group	RG1

Electrical data

Power consumption (W)	2.2
Wattage (W)	2.2
Equivalent watt (W)	50
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Control gear required	No
Dimmable	Yes
Inrush Current (A)	2.6
Inrush Duration (µs)	340
Lamp Energy Label (class)	В
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Lifespan L70 B50 50000

Physical data

IP rating	IP20
Nominal Product Length (mm)	54
Nominal Product Diameter (mm)	50
Weight (kg)	0.046

RefLED Platinum Retro ES50 350LM DIM 830 36 SL

Item No: 0030370



Packaging

5 5	
Product EAN number	5410288303703
Packaging single length / height (cm)	8.2
Packaging single width (cm)	6.1
Packaging single depth (cm)	5.1
DUN14 (inner)	15410288303700
Units per inner package	6
Packaging inner length / height (cm)	19.4
Packaging inner width (cm)	11.3
Packaging inner depth (cm)	9.5
DUN14 (outer)	25410288303707
Units per outer package	60
Packaging outer length / height (cm)	58.8
Packaging outer width (cm)	21.8
Packaging outer depth (cm)	21.7

Safety data

Optimal operating condition (°C)	-20-50
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Dimmable with approved dimmers