ToLEDo Vintage T32 DIM 550LM E27 SL

Item No: 0030156


















Experience enchanting Flexible Filament LED lamps, blending timeless charm with cutting-edge technology -say goodbye to ordinary LED filament lamps! Sylvania ToLEDo™ Vintage lamps boast superior design, higher lumen output, making them perfect for general illumination, creating cosy ambience and decorative lighting. Illuminate your living rooms, dining areas, and kitchens at home with elegance or create a captivating ambience in hotels, restaurants, bars, and heritage spaces. High Lumen output -550lm 15,000 hours average rated life -last 7.5 times longer than incandescent vintage lamps Replace up to 45W incandescent lamps with ease, while enjoying dimmable lighting with approved dimmers. Environment friendly – no mercury and lower CO2 emissions Backed by a 3-year warranty for complete peace of mind.

Technical Assets

Dimensions (mm)



Photometrics

ToLEDo Vintage T32 DIM 550LM E27 SL

Item No: 0030156



Ge	ne	ral	ld	ata

Product name	ToLEDo Vintage T32 DIM 550LM E27 SL
Technology	LED
Lamp shape	Straight
Cap/Base	E27
Lamp finish	Other
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C+40°C
ETIM Class	EC001959
Warranty	3 years

Optical data

Useful luminous flux (Φuse)	550
Correlated colour temperature (k)	2000
Light colour	Candlelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	330
Photobiological Risk Group	RG1

Electrical data

Electrical data		
Power consumption (W)	7	
Wattage (W)	7	
Equivalent watt (W)	45	
Primary Supply/Product voltage - min (V)	220	
Primary Supply/Product voltage - max (V)	240	
Control gear required	No	
Dimmable	Yes	
Inrush Current (A)	0.26	
Inrush Duration (µs)	330	
Lamp Energy Label (class)	G	
Nominal Frequency (Hz)	50/60Hz	

Lifetime data

Physical data

IP rating	IP20
Nominal Product Height (mm)	185
Nominal Product Diameter (mm)	32
Weight (kg)	0.05

Packaging

5410288301563
3.9
3.9
20.0
15410288301560
6
12.5
8.5
21.0

Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	Yes
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures