ToLEDo Vintage G200 450LM GL 820 SST

Item No: 0030111
















SvISmart



Indulge in the allure of a vintage-inspired LED filament lamp, with gold-tinted glass construction and sleek spiral design for timeless charm and eco-friendly illumination. Creates a warm and inviting ambiance and adds a touch of classic elegance to your home. Works effortlessly with SylSmart Home App, SylRemote, Amazon Alexa, Google Assistant and Siri Shortcuts for seamless control and convenience. Set the brightness level from 1% to 100% with wireless dimming feature for the ideal lighting experience.

Technical Assets

Dimensions (mm)



Photometrics

ToLEDo Vintage G200 450LM GL 820 SST

Item No: 0030111



| Genera | l da | ata |
|--------|------|-----|
|--------|------|-----|

| Product name | ToLEDo Vintage G200 450LM GL 820 SST |
|----------------------------------|--|
| Technology | LED |
| Lamp shape | Round/globe |
| Cap/Base | E27 |
| Lamp finish | Other |
| Fixture rating | Open |
| General application | Hospitality, Residential & Consumer, Retail |
| Operating temperature range (°C) | -20°C+40°C |
| ETIM Class | EC001959 |
| E-number FI | 4741198 |
| Warranty | 3 years |

Optical data

| - | |
|-----------------------------------|-------------|
| Useful luminous flux (Φuse) | 450 |
| Correlated colour temperature (k) | 2000 |
| Light colour | Candlelight |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM6 |
| Photobiological Risk Group | RG1 |

Electrical data

| Electrical data | |
|--|---------|
| Power consumption (W) | 7.5 |
| Wattage (W) | 7.5 |
| Equivalent watt (W) | 40 |
| Current (A) | 0.055 |
| Primary Supply/Product voltage - min (V) | 220 |
| Primary Supply/Product voltage - max (V) | 240 |
| Control gear required | No |
| Dimmable | Yes |
| Inrush Current (A) | 2.9 |
| Inrush Duration (µs) | 730 |
| Lamp Energy Label (class) | G |
| Nominal Frequency (Hz) | 50/60Hz |
| | |

Lifetime data

Lifespan L70 B50 15000

Physical data

| IP rating | IP20 |
|-------------------------------|-------|
| Nominal Product Length (mm) | 186 |
| Nominal Product Diameter (mm) | 200 |
| Weight (kg) | 0.331 |

Packaging

| Product EAN number | 5410288301112 |
|---------------------------------------|----------------|
| Packaging single length / height (cm) | 22.3 |
| Packaging single width (cm) | 22.3 |
| Packaging single depth (cm) | 31.8 |
| DUN14 (inner) | 15410288301119 |
| Units per outer package | 2 |
| Packaging outer length / height (cm) | 46.7 |
| Packaging outer width (cm) | 23.8 |
| Packaging outer depth (cm) | 33.8 |

Safety data

| Optimal operating condition (°C) | -20-40 |
|-------------------------------------|--|
| Breakage cleaning instructions | Not applicable |
| Special purpose lamp | No |
| Dry applications use only | Yes |
| Suitable for household illumination | Yes |
| Safety message | Not Suitable for totally enclosed fixtures |
| | |