

Blacklight BL368 Linear T8

F30W T8 BL368

0000098



Range Features

- Features
- BL368 tubes emit an upgraded highly concentrated radiation with peak around 368 nm. Flying insects eye sensitivity is generally at or near this frequency
- 100% improvement in effectiveness (at 368nm)
- Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)
- Performs longer and better throughout the insect season
- Same shape, structural and electrical characteristics and control circuits as standard T12,T8 or T5 tubes
- Applications
- Insect traps, insect attraction is strongly increased
- Restaurants, kitchens, food shops, supermarkets
- Diazo printing machines
- Photo Polymerisation
- Chemical processing
- Mineral detection
- Various technical applications
- Directions for use
- Maximum exposure limits are set by EN60335-2-59:1997 at an effective 1.0 milliWatt per metre squared (1.0 mW/m²) measured at a distance of 1 metre originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0.2 and 0.4 mW/m² depending on the wattage



PRODUCT OVERVIEW

Lampenoberfläche	Beschichtet
Lampenform	Tubular
Farbtemperatur (K)	UV-A lamp
Dimmbar	YES
EAN-Code	5410288000985
Verschluss/Socket	G13
Typ	BL368
Watt (Nennleistung) (W)	30
Bestellnummer	0000098
Technologie	Fluorescent
Spannung (V)	96

DATENTABELLE

Allgemeine Daten

Blacklight BL368 Linear T8

F30W T8 BL368

0000098

Betriebsgerät erforderlich	Ja
Lampenoberfläche	Beschichtet
Lampenform	Tubular
Dimmbar	YES
EAN-Code	5410288000985
Allgemeiner Einsatz	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer
Einsatzzweck	Special lighting
Verschluss/Socket	G13
Typ	BL368
Bestellnummer	0000098
Lange Bezeichnung	<p>Features</p> <p>BL368 tubes emit an upgraded highly concentrated radiation with peak around 368 nm. Flying insects eye sensitivity is generally at or near this frequency</p> <p>100% improvement in effectiveness (at 368nm)</p> <p>Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)</p> <p>Performs longer and better throughout the insect season</p> <p>Same shape, structural and electrical characteristics and control circuits as standard T12,T8 or T5 tubes</p> <p>Applications</p> <p>Insect traps, insect attraction is strongly increased</p> <p>Restaurants, kitchens, food shops, supermarkets</p> <p>Diazo printing machines</p> <p>Photo Polymerisation</p> <p>Chemical processing</p> <p>Mineral detection</p> <p>Various technical applications</p> <p>Directions for use</p> <p>Maximum exposure limits are set by EN60335-2-59:1997 at an effective 1.0 milliWatt per metre squared (1.0 mW/m²) measured at a distance of 1 metre originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0.2 and 0.4 mW/m² depending on the wattage</p>
Produktname	F30W T8 BL368
Lampen für spezielle Einsatzbereiche	Yes
Technologie	Fluorescent
Menge/Verpackungseinheit	25
E-Nummer FI	4940427
Optische Daten	
Farbtemperatur (K)	UV-A lamp
Elektrische Daten	
Watt (Nennleistung) (W)	30

Blacklight BL368 Linear T8

F30W T8 BL368

0000098

Spannung (V) 96

Physikalische Daten

Verpackungsbezeichnung Box/Sleeve

Gewicht (kg) 0.12

TECHNISCHE ZEICHNUNGEN

