

## Grolux T8

F36W/GRO Retail

**0000712**



### Range Features

- High level of blue and red radiation helps promote healthy plant growth
- Strengthens the natural colours of aquatic plants and fish in aquariums
- Promotes the process of photo-synthesis in plants
- Oldest, but most optimal light colour for plants and aquaria
- Applications
- For lighting of fresh water aquariums
- Complete or additional artificial lighting of plants
- Recommended for use in greenhouses, indoor gardens, flower shows and conservatories



### PRODUCT OVERVIEW

Lamp finish	Coated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288007120
Cap/Base	G13
Type	GroLux
Watt (Nominal) (W)	36
Ordering number	0000712
Technology	Fluorescent
Voltage (V)	103

### DATA TABLE

#### General data

Average life (Nominal) (h)	10000
Control gear required	Yes
Lamp finish	Coated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288007120
Fixture rating	Open
General application	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer
IEC Reference	Special lighting
Intended purpose	Special lighting
Cap/Base	G13
Lamp mercury content (mg)	10

## Grolux T8

F36W/GRO Retail

### 0000712

<b>Type</b>	GroLux
<b>Ordering number</b>	0000712
<b>Range features</b>	High level of blue and red radiation helps promote healthy plant growth Strengthens the natural colours of aquatic plants and fish in aquariums Promotes the process of photo-synthesis in plants Oldest, but most optimal light colour for plants and aquaria Applications For lighting of fresh water aquariums Complete or additional artificial lighting of plants Recommended for use in greenhouses, indoor gardens, flower shows and conservatories
<b>Product name</b>	F36W/GRO Retail
<b>Special purpose lamp</b>	Yes
<b>Technology</b>	Fluorescent
<b>Transformer required</b>	No
<b>Sales pack quantity</b>	10

#### Electrical data

<b>Current (A)</b>	0.43
<b>Watt (Nominal) (W)</b>	36
<b>Watt (Rated) (W)</b>	36
<b>Voltage (V)</b>	103

#### Physical data

<b>Max. Lamp Diameter (mm) - D</b>	26
<b>Lamp Length (mm) - C/L</b>	1213.6
<b>Length base to base (mm) - A</b>	1199.4
<b>Length base to pin Min-Max - B</b>	1204.1-1206.5
<b>Single packaging type</b>	Box/Sleeve
<b>Weight (kg)</b>	0.16

## TECHNICAL DRAWINGS

